



1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VAICO VA-DOT 4+

VAICO No.:

V60-0243, V60-0235, V60-0236, V6-0237, V60-0446

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

- 2.1. **Low viscosity guarantees perfect functioning of systems.**
- 2.2. **Synthetic fluid.**
- 2.3. **Excellent thermal stability.**
- 2.4. **Optimum protection for all metal parts in the brake system against corrosion.**
- 2.5. **Unrivalled oxidation stability and optimised hygroscopic properties ensure high safety margin.**
- 2.6. **Compatible with all seals and hoses installed in the brake system.**

3. USE INSTRUCTIONS

VAICO VA-DOT 4+ has been specially designed for use in heavy-duty brake systems of vehicles that require a DOT 4 synthetic brake fluid. The product is particularly recommended for brake systems with ESP/DSC, ASR and ABS. VAICO VA-DOT 4+ can be mixed with all synthetic brake fluids of the same grade.

3.1. Special instructions:

- 3.1.1. Store brake fluid only in sealed original container.
- 3.1.2. Brake fluid can cause damage to vehicle paintwork.
- 3.1.3. Observe manufacturer instructions!

4. PERFORMANCE DATA

Specifications:

FMVSS 116 DOT 3/ DOT 4 | SAE J 1703 / J 1704 | ISO 4925 Class 6

Suitable for:*

AUDI-VW B 000 750 M1 | **MB** 331.0, 000 989 08 07, 000 989 08 07 17

VOLVO 9 437 430, 9 437 431, 9 437 433, 9 437 434



PRODUCT DATA



TYPICAL VALUES	METHOD	UNIT	VAICO VA-DOT 4+
Density at 20°C	DIN 51 757	g/cm ³	1.060
Viscosity at -40°C	DIN ISO 3104	mm ² /s	max. 700
Dry boiling point (min.)	DIN ISO 4925	°C	265
Wet boiling point (min.)	DIN ISO 4925	°C	175

* conforms to OEM specifications – The above values may vary within commercially accepted tolerances.