

WOLF GUARDTECH 20W50 SHPD

11/08/2023
1247

Multigrade engine oil, suitable for all diesel engines in all working conditions and during the whole year. Due to the high content of active components, this oil can be used all year round in the toughest conditions. Because of the high resistance against ageing, it is possible to apply longer drain periods.

APPLICATIONS

This oil is suitable for all diesel engines with natural aspiration or turbocharging, in all working conditions in all seasons and long drain periods. It is also suitable for most gasoline engines.

FEATURES

Total engine protection: performance in keeping the engine clean
Drain interval extension: long period between oil change

PERFORMANCE

ACEA	A3/B3-10	DAIMLER TRUCK	DTFR 15B110
ACEA	A3/B4-08	MACK	EO-L
ACEA	E3-96 Issue 4	MAN	271
API	CF-4/SG	MAN	M3275-1
API	CG-4/SJ	MB	227.1
MIL	L-2104 E	MB	228.1
MIL	L-46152 E	MB	228.3
ALLISON	C4 Level	MB	229.1
CATERPILLAR	TO-2	MTU	Oil Category 1
CUMMINS	CES 20071	MTU	Oil Category 2
CUMMINS	CES 20072	VOLVO	VDS-2

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.891
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	150
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	17.7
Viscosity index	ASTM D2270		130
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	8.5
Pour point	ASTM D6892	°C	-33
CCS viscosity at -15°C	ASTM D5293	mPa.s	8200
Sulfated Ash	ASTM D874	Mass %	1.18
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

