

WOLF OFFICIALTECH 75W80

11/08/2023
23300

This is an extreme-pressure lubricant for gear boxes, specially formulated, made of specially selected, high-quality base oils and a customized additive package, to satisfy the highest service conditions: high speed, shockloads, high torque at low speeds and multiple synchronesh compatibility.

APPLICATIONS

It is recommended for all hypoid transmissions and is also suitable for spiral bevel gear, worm wheels and most transaxles.

FEATURES

Frictional properties: smooth shift performance
Anti-wear protection: long transmission life
Extended oil life: proven resistance to oil degradation

PERFORMANCE

API	GL-5	OPEL	GM 1940757
MIL	L-2105 D	OPEL	GM 1940768
BMW	23001434404	OPEL	GM 1940776
BMW	23007533513/818	VOLVO	97308
BMW	83220309031	VW	501 50
BMW	83220403247	VW	G 005 000
BMW	83227533818	VW	G 052 532
FORD	WSD-M2C200-C/C2/C3	VW	G 052 911
OPEL	GM 1940182		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.877
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	54.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	10.5
Viscosity index	ASTM D2270		186
Pour point	ASTM D6892	°C	-51
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	45000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

