

WOLF VITALTECH ATF D III PC

26/08/2023
3009

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This is an oil with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

APPLICATIONS

This oil is used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements.

FEATURES

Frictional properties: smooth shift performance.
Anti-wear protection: extended transmission life.
Extended oil life: excellent thermal and oxidation stability.

PERFORMANCE

| | | | |
|---------------|---------------|------|--------------|
| DAIMLER TRUCK | DTFR 13C120 | FORD | MERCON |
| FORD | ESP-M2C138-CJ | GM | DEXRON III-H |
| FORD | ESP-M2C166-H | MB | 236.2 |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|-------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.849 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 32.0 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 6.82 |
| Viscosity index | ASTM D2270 | | 181 |
| Pour point | ASTM D6892 | °C | -51 |
| Brookfield viscosity at -40°C | ASTM D2983 | mPa.s | <=20000 |
| Flash Point COC | ASTM D92 | °C | 198 |
| Colour | VISUAL | | RED |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

