

WOLF ECOTECH MULTI VEHICLE ATF FE

22/08/2023
3014

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions with a high viscosity index, excellent oxidation stability, excellent friction and anti-wear properties providing excellent fuel economy and meeting the requirements of most American, Japanese and European manufacturers.

APPLICATIONS

Its versatile nature guarantees it can be used in the latest generations of automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: significantly extended transmission life
Extended oil life: excellent thermal and oxidation stability

PERFORMANCE

AISIN-WARNER	AW-1	GM	DEXRON VI
AISIN-WARNER	AW-2	HONDA	DW-1
AISIN-WARNER	JWS 3324	HYUNDAI	NWS-9638 T5
ALLISON	C4	HYUNDAI	SPH-IV
BMW	83 22 0 397 114	HYUNDAI	SP-IV
BMW	83 22 2 305 397	ISUZU	WSI
BMW	83 22 9 407 858	JAGUAR	02JDE26444
BMW	83222152426	LAND ROVER	LR023288
BMW	83222167718	MAZDA	FZ
BMW	83222413477	MB	236.12
BMW	ATF 3	MB	236.41
BMW	ATF 7	MINITUBISHI	ATF J3
BMW	L 12108	NISSAN	MATIC-5
BMW	M-1375.4	PSA	1635056080
CHRYSLER	68157995AA	TESLA	ATF9/EDF2
FIAT	9.55550-AV2	TOYOTA	AUTO FLUID WS
FIAT	9.55550-AV5	VOLVO	31492172
FORD	MERCON LV	VOLVO	31492173
FORD	MERCON SP	VW	G 053 001
FORD	WSS-M2C195-A	VW	G 055 005
FORD	WSS-M2C924-A	VW	G 055 162
FORD	WSS-M2C938-A	VW	G 055 540
GM	DEXRON HP	VW	G 060 162

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	32.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6.45
Viscosity index	ASTM D2270		156
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

