

# WOLF EXTENDTECH ATF D II LD

26/08/2023  
3023

This is an oil with a high viscosity index for automatic transmissions. It is characterized by a high chemical stability, increased anti-wear properties and an excellent resistance against ageing.

## APPLICATIONS

It can be used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron II-D and Type A suffix A requirements.

## FEATURES

Anti-wear protection: extended transmission life  
Extended oil life: optimized thermal and oxidation stability

## PERFORMANCE

DAIMLER TRUCK	DTFR 13C120	GM	6137-M DEXRON II-D
FORD	ESP-M2C138-CJ	GM	DEXRON TYPE A, SUFFIX A
FORD	MERCON	MB	236.2
GM	6032-M DEXRON		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.847
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	32.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6.82
Viscosity index	ASTM D2270		181
Pour point	ASTM D6892	°C	-51
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	14500
Flash Point COC	ASTM D92	°C	199
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.