

WOLF OFFICIALTECH OW30 SP

04/09/2023
65646

This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is specifically formulated to meet both the BMW Longlife-12 FE and the Ford WSS M2C950-A specification. It is adapted to meet the requirements of the latest technology, highly engineered turbo engines requiring high performance and lower viscosity oils.

APPLICATIONS

This product is mandatory in the newest BMW and Ford gasoline and diesel engines. It provides a multi vehicle application through the ACEA C2 specification. Optimum formulation for today's cars with exceptional film strength preventing oil film breakdown and reducing friction providing fuel economy and reliability.

FEATURES

Total engine protection: performance in keeping the engine clean.

Fuel economy: superior fuel economy and CO2 reduction.

Cold start: excellent fluidity at low temperature.

PERFORMANCE

ACEA	C2	KIA	.
API	SN Plus	LANCIA	.
API	SP	LEXUS	.
ILSAC	GF-5	MASERATI	.
ALFA ROMEO	.	MB	approval 227.61
BMW	approval LONGLIFE-12 FE	MB	approval 229.61
DAIMLER TRUCK	DTFR 15D100	MINI	.
FIAT	9.55535-DS1	MITSUBISHI	.
FIAT	9.55535-GS1	OPEL	OV 040 1547 - G30
FORD	WSS-M2C950-A	ROLLS-ROYCE	.
GENESIS	.	SsangYong	.
HONDA	.	SUBARU	.
HYUNDAI	.	SUZUKI	.
JAGUAR-LAND ROVER	STJLR.03.5007	TOYOTA	.
JEEP	.	VW	530 35

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.843
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	48.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	9.8
Viscosity index	ASTM D2270		194
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	9.4
Pour point	ASTM D6892	°C	-48
Flash Point COC	ASTM D92	°C	224

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

