

# WOLF OE LEVELTECH OW-30 MS-BHDI

10/10/2023  
75637

This lubricant is based on carefully selected very high quality base oils, specially developed for the PSA EURO VI Blue HDi DW10F engines with exhaust after treatment and turbocharger. This specification demands high stability to ensure long oil drain intervals. It also addresses the use of biofuels.

## APPLICATIONS

This engine oil is primarily developed for mandatory use in the PSA EURO VI Blue HDi DW10F engines and particularly ones equipped with e-HDI using Stop & Start technologies. This oil is also usable for other OEM's passenger cars requiring this viscosity grade and ACEA C2 performance, thus providing a multi vehicle oil application. Optimum formulation for today's cars with extended service intervals.

## FEATURES

Total engine protection: performance in keeping the engine clean

Fuel economy

: superior fuel economy and CO<sub>2</sub> reduction

Cold start: excellent fluidity at low temperature

## PERFORMANCE

|      |             |       |                       |
|------|-------------|-------|-----------------------|
| ACEA | C2          | IVECO | 18-1811 Classe SC1 LV |
| FIAT | 9.55535-DS1 | PSA   | B71 2312              |
| FIAT | 9.55535-GS1 |       |                       |

## TYPICAL CHARACTERISTICS

| Test                         | Method     | Unit               | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C              | ASTM D4052 | g/ml               | 0.844           |
| Kinematic viscosity at 40°C  | ASTM D445  | mm <sup>2</sup> /s | 50.1            |
| Kinematic viscosity at 100°C | ASTM D445  | mm <sup>2</sup> /s | 9.6             |
| Viscosity index              | ASTM D2270 |                    | 180             |
| Pour point                   | ASTM D6892 | °C                 | -42             |
| Sulfated Ash                 | ASTM D874  | Mass %             | 0.56            |
| Flash Point COC              | ASTM D92   | °C                 | 226             |
| CCS viscosity at -35°C       | ASTM D5293 | mPa.s              | 5950            |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfubes.com](http://www.wolfubes.com)

