

CHAMPION NEW ENERGY ATF D III PC

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This is an oil with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

APPLICATIONS

This oil is used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements.

FEATURES

Frictional properties: smooth shift performance.

Anti-wear protection: extended transmission life.

Extended oil life: excellent thermal and oxidation stability.

PERFORMANCE

FORD	ESP-M2C138-CJ	GM	DEXRON III-H
FORD	ESP-M2C166-H	MB	236.2
FORD	MERCON		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.849
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	32.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6.82
Viscosity index	ASTM D2270		181
Pour point	ASTM D6892	°C	-51
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	198
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

