

CHAMPION ACTIVE DEFENCE SAE 40

This is a straight mineral oil, made of highly refined base oils.

APPLICATIONS

Non-detergent engine oil, also for not heavily loaded gearboxes. Lubrication by hand [oilcan]. Lubrication of air compressors with low discharge temperatures or when an oil of DIN-VC-class is required.

FEATURES

Total engine protection: engine protection and cleanliness

PERFORMANCE

API SA

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.891 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 140 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 13.7 |
| Viscosity index | ASTM D2270 | | 93 |
| Pour point | ASTM D6892 | °C | -12 |
| Flash Point COC | ASTM D92 | °C | 260 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

