

# CHAMPION OEM SPECIFIC 0W30 SP

This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is specifically formulated to meet both the BMW Longlife-12 FE and the Ford WSS M2C950-A specification. It is adapted to meet the requirements of the latest technology, highly engineered turbo engines requiring high performance and lower viscosity oils.

## APPLICATIONS

This product is mandatory in the newest BMW and Ford gasoline and diesel engines. It provides a multi vehicle application through the ACEA C2 specification. Optimum formulation for today's cars with exceptional film strength preventing oil film breakdown and reducing friction providing fuel economy and reliability.

## FEATURES

Total engine protection: performance in keeping the engine clean.

Fuel economy: superior fuel economy and CO<sub>2</sub> reduction.

Cold start: excellent fluidity at low temperature.

## PERFORMANCE

ACEA	C2	KIA	.
API	SN Plus	LANCIA	.
API	SP	LEXUS	.
ILSAC	GF-5	MASERATI	.
ALFA ROMEO	.	MB	approval 227.61
BMW	approval LONGLIFE-12 FE	MB	approval 229.61
DAIMLER TRUCK	DTFR 15D100	MINI	.
FIAT	9.55535-DS1	MITSUBISHI	.
FIAT	9.55535-GS1	OPEL	OV 040 1547 - G30
FORD	WSS-M2C950-A	ROLLS-ROYCE	.
GENESIS	.	SsangYong	.
HONDA	.	SUBARU	.
HYUNDAI	.	SUZUKI	.
JAGUAR-LAND ROVER	STJLR.03.5007	TOYOTA	.
JEEP	.	VW	530 35

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION**  
LUBRICANTS



## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.843
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	48.3
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.8
Viscosity index	ASTM D2270		194
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	9.4
Pour point	ASTM D6892	°C	-48
Flash Point COC	ASTM D92	°C	224

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

