| DIEGE | BOSCH Delphi Diesel Center Technologies | DENSO Stanadyne |
|---------|---|-----------------|
| (T) BUC | HLI | |
| | | |
| | | |

| Product info s | heet | Robert Bosch | 0445110175 |
|----------------------------|--------------------|----------------------|-----------------|
| Special tools needed? | Yes | | |
| Mounting tools to fix inje | ectors while tight | en injectors | |
| | | | |
| | Pro | duct specific inforr | mation |
| Programming | No | | |
| | | | |
| Unlocking | No | | |
| Adaption values reset | No | | |
| Bleed | No | | |
| adjustment at mounting | _1 Yes | | |
| adjustment at mounting | _2 | Tightening torque | ies |
| Injector/ retainingclamp | | 40 Nm, loosen | n, second 32 Nm |
| High Pressure pipe nuts | | 25 Nm | |
| Bolts valve cover | | 10 Nm | |
| Bolts sealing injector | | 1: 10 Nm 2: 19 | 9 Nm |
| | | Assembly instructi | ions |
| Replace sealing washer | | | |
| Recommendation: replace | ce seals in valve | cover | |
| Core charge terms: | | | |

- -externally intact,
- -no mechanical damage,
- -not dismantled,
- -no heavy corrosion.







YANMAR