

Attention: 2 bolts hold 3 injectors. Bolts are different. Product specific informat Programming Yes C3I code (20 characters) Unlocking Adaption values reset Bleed Adaption values reset Bleed adjustment at mounting_1 No adjustment at mounting_2	28+24ø49 1-91JHØ1F81 29 0002LC3 2777J 87528892EA7 6KPSCYCYX
Product specific informat Programming Yes C3I code (20 characters) Unlocking Adaption values reset Bleed Activate feed pump by OBD adjustment at mounting_1 Adjustment at mounting_2	28+24049 1-913-115-81 28+24049 1-913-115-81 28-24-01-9 1-913-81 28-24-01-9 1-913-81 28-24-
Programming Yes C3I code (20 characters) Unlocking Adaption values reset No Pres No Activate feed pump by OBD Activate feed pump by OBD Adjustment at mounting_1	28424ø49 1491JHØ1F81 2000000000000000000000000000000000000
Programming Yes C3I code (20 characters) Unlocking Adaption values reset No Bleed Activate feed pump by OBD Activate feed pump by OBD Activate feed pump by OBD	28+24Ø49 1-91JHØ1F81 28-2730 87528892EA7 6KPSCYCYX
Programming Yes C3I code (20 characters) Unlocking Adaption values reset No Pres Activate feed pump by OBD Activate feed pump by OBD Adjustment at mounting_1 Adjustment at mounting_2	28+24Ø49 1-91JHØ1F81 29 DØØ2LC3 4 ØLB13Ø 277J 87528CYCYX
Unlocking Adaption values reset No Bleed Yes Activate feed pump by OBD Adjustment at mounting_1 Adjustment at mounting_2	28+24049 14913H01F81 9 404B130 2773 B7528B92EA7 6KPSCYCYX
Adaption values reset No Bleed Yes Activate feed pump by OBD Adjustment at mounting_1 Adjustment at mounting_2	B7528B92EA7 6KPSCYCYX
Adaption values reset Bleed Yes Activate feed pump by OBD Activate feed pump by OBD Adjustment at mounting_1	B7528892EA7
Activate feed pump by OBD No adjustment at mounting_2 Activate feed pump by OBD	
ndjustment at mounting_1 No	
djustment at mounting_2	
T. 1.	
T. 1.	
T' 1	
Tightening torques	
Injector/ retainingclamp 9 Nm + 180°	
High Pressure pipe nuts	
Accombly instructions	
Assembly instructions	
Replace tension bolts Recommendatio Replace sealing washer Recommendatio	ni roniaco coaling ring

Core charge terms:

- -externally intact,
- -no mechanical damage,
- -not dismantled,
- -no heavy corrosion.