

# GASKET MATERIALS CORTECO 5000

EN

## Examples of use

Cylinder head gaskets, exhaust seals, to counter environments of very high temperatures.

Maximum temperature: 600 °C and up to 1000 °C in inert or reduced atmospheres.

## Composition

Two sheets of exfoliated graphite stapled to two sheets of perforated galvanised steel.

FR

## Exemples d'utilisation

Joints de culasse, joints d'échappement. Solution à des sollicitations thermiques sévères. Limite de température : 600 °C, jusqu'à 1000 °C en atmosphère inerte ou réductrice.

## Composition

Matériau constitué de deux feuilles de graphite exfolié, agrafées de part et d'autre d'une tôle en acier zingué perforée.

DE

## Verwendungsbeispiele

Zylinderkopfdichtungen, Auspuffdichtungen, um Probleme bei sehr hohen Temperaturen entgegenzuwirken. Höchsttemperatur: 600 °C bis 1000 °C in inerten oder reduzierten Atmosphären.

## Zusammensetzung

Zwei Bögen von Blähgraphit auf zwei Bleche aus perforiertem verzinktem Stahl geheftet.

IT

## Esempio d'utilizzo

Guarnizioni della testata, Giunti di scappamento, Soluzione a sforzi termica rigorose. Limite di temperatura: 600 °C, fino a 1000 °C in atmosfera inerte o riduttrice.

## Composizione

Materiale costituito di due strati di grafite sfogliata, attaccati da ambo le parti di una lamiera in acciaio zincato perforata.



|        |     |            |
|--------|-----|------------|
|        |     | 33 x 50 cm |
| 1,2 mm | x 1 | 416152P    |