

# VITALTECH

## 10W60 M

22/05/2017  
16128

This is a full synthetic lubricant based on carefully selected very high quality base oils of the latest generation, for the lubrication of all gasoline and diesel engines with turbo.

### APPLICATIONS

4 stroke gasoline engines, multi-valves, turbo. 4 stroke diesel engines, with or without turbo.

### FEATURES

Cold start : very good fluidity at low temperature.  
Total engine protection : outstanding engine cleanliness and durability.

### SPECIFICATION LEVEL

ACEA	A3/B4-08	MB	229.3 Level
API	SN/CF	VW	501 01
BMW	M-MODELS	VW	505 00
BMW	LONGLIFE-01 Level		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.855
Kinematic viscosity at 40°C	ASTM D445	mm²/s	156
Kinematic viscosity at 100°C	ASTM D445	mm²/s	25.0
Viscosity index	ASTM D2270		194
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	9.5
Pour point	ASTM D6892	°C	-36
CCS viscosity at -25°C	ASTM D5293	mPa.s	3800
Sulfated Ash	ASTM D874	Mass %	1.0
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

