

WOLF GUARDTECH

SAE 40 CF-4/SG

11/08/2023
21204

Monograde motor oil of high quality, suitable for diesel engines (supercharged or naturally aspirated) and gasoline engines in all circumstances.

APPLICATIONS

This oil is particularly recommended for fixed diesel engines, material for public works and for mixed fleets of trucks and cars.

FEATURES

Total engine protection: engine protection and cleanliness

PERFORMANCE

API	CF-4/SG	MIL	L-46152 E
MIL	L-2104 E	MB	227.0

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.900
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	136
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14
Viscosity index	ASTM D2270		100
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	7.6
Pour point	ASTM D6892	°C	-27
Sulfated Ash	ASTM D874	Mass %	1.10
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

