WOLF ANH CA GREASE EP 1

09/07/2024 9226

This high quality multipurpose grease can be used in both industrial and automotive applications. The grease is suitable for a wide range of plain and rolling bearings.

APPLICATIONS

The ANH Ca thickener, together with the special base oil blend, makes this grease suitable for the lubrication of medium loaded bearings and in wet and corrosive environments. This lubricating grease has excellent adhesion and water resistance.

FEATURES

Corrosion protection: very good corrosion protection. Multi-applicability: wide range of use. Water resistance: excellent resistance against water washout.

SPECIFICATIONS

DIN	51502	ISO	12924
DIN	КР1К-30	ISO	L-XC(F)CIB1

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Texture	Visual		SMOOTH
Colour	VISUAL		Yellow Brown
NLGI Classification	ASTM D217		1
Worked Penetration (60 strokes)	ISO 2137	0.1 mm	310-340
Dropping point	ISO 2176/IP 396	°C	> 140
Four Ball Weld Load	ASTM D2596/ DIN51350:4	Ν	3000
Base Oil Viscosity at 40 °C	ASTM D7152	cSt	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV G. Gilliotstraat 52 – 2620 Hemiksem – Belgium Tel. +32 (0)3 870 00 00 www.wolflubes.com

