

# WOLF ELECTRUM TRANS FLUID

11/08/2023  
65301

This is a full synthetic lubricant based on carefully selected very high quality base oils, especially formulated for automatic transmissions in electric cars (e-ATF) and hybrid cars. It provides excellent frictional durability and superior performance.

## APPLICATIONS

This ATF is specifically recommended for automatic transmissions in electric vehicles (e-ATF) and hybrid vehicles.

## FEATURES

Optimum electrical properties: allowing high voltages applications.

Frictional properties: very smooth gear shifting, no vibration.

Extended oil life: excellent thermal and oxidation stability.

## PERFORMANCE

/ /

## TYPICAL CHARACTERISTICS

| Test                          | Method     | Unit               | Average results |
|-------------------------------|------------|--------------------|-----------------|
| Density at 15°C               | ASTM D4052 | g/ml               | 0.845           |
| Kinematic viscosity at 40°C   | ASTM D445  | mm <sup>2</sup> /s | 31.0            |
| Kinematic viscosity at 100°C  | ASTM D445  | mm <sup>2</sup> /s | 6.2             |
| Viscosity index               | ASTM D2270 |                    | 160             |
| Pour point                    | ASTM D6892 | °C                 | -45             |
| Brookfield viscosity at -40°C | ASTM D2983 | mPa.s              | 11800           |
| Colour                        | VISUAL     |                    | RED             |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfubes.com](http://www.wolfubes.com)

