

WOLF VITALTECH 15W40

29/06/2023
14636

This is a high-performance mineral diesel engine oil formulated to deliver reliable performance in a broad range of heavy-duty applications. It is suitable for low-emission engines (Euro II, Euro III and some Euro IV engines).

APPLICATIONS

Recommended for all modern diesel engines of trucks, off-road equipment and other heavy-duty applications. Universal use, including mixed fleets. Suitable for low-emission diesel engines with EGR (Euro II, III and some Euro IV). Meets and exceeds the demanding requirements of many U.S. and European diesel engine manufacturers.

FEATURES

Total engine protection: outstanding engine cleanliness and durability

SPECIFICATIONS

CUMMINS	CES 20076	CATERPILLAR	ECF-2
CUMMINS	CES 20077	MB	229.1
CUMMINS	approval CES 20078	MB	approval 228.3
MACK	approval EO-N	ALLISON	C4
MACK	EO-M PLUS	MAN	M3275-1
MTU	approval Oil Category 2	IVECO	18-1804 Classe T2 E7
RENAULT	RLD	ACEA	A3/B4
RENAULT	approval RLD-2	ACEA	E7
VOLVO	approval VDS-3	DEUTZ	approval DQC-III-18
API	CG-4	DETROIT DIESEL	DFS 93K215
API	CH-4	API	CF-4
API	approval CI-4/SL	CATERPILLAR	TO-2
JASO	DH-1	MACK	EO-L
DEUTZ	DQC-III-10	MTU	Oil Category 1
GLOBAL	DHD-1	DAIMLER TRUCK	approval DTFR 15B110
CATERPILLAR	ECF-1a		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.886
Kinematic viscosity at 40°C	ASTM D445	mm²/s	97
Kinematic viscosity at 100°C	ASTM D445	mm²/s	13.8
Viscosity index	ASTM D2270		144
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-36
CCS viscosity at -20°C	ASTM D5293	mPa.s	6500
Sulfated Ash	ASTM D874	Mass %	1.49
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

