

CHAMPION OEM LEVEL 5W30 C4

This full synthetic engine oil is formulated to meet the specifications of different OEMs. The low SAPS formula guarantees complete DPF protection. Furthermore, its fluidity at low temperatures guarantee easy starting in winter conditions.

APPLICATIONS

Can be used for gasoline and diesel engines of passenger cars, more specifically for Renault, requiring the ACEA C4 and RN 720 specifications.

FEATURES

Aftertreatment protection: aftertreatment system compatible

Total engine protection: outstanding engine cleanliness and durability

PERFORMANCE

| | | | |
|-------------|------------|----------------|---------|
| ACEA | C3 | MB | 229.31 |
| ACEA | C4 | MB | 229.51 |
| FIAT | 9.55535-S4 | RENAULT | RN 0720 |
| MB | 226.51 | | |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|----------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.851 |
| Kinematic viscosity at 40°C | ASTM D445 | mm²/s | 69.1 |
| Kinematic viscosity at 100°C | ASTM D445 | mm²/s | 11.7 |
| Viscosity index | ASTM D2270 | | 165 |
| B.N. [HClO4 method] | ASTM D2896 | mg KOH/g | 7.2 |
| Pour point | ASTM D6892 | °C | -45 |
| Sulfated Ash | ASTM D874 | Mass % | 0.5 |
| Flash Point COC | ASTM D92 | °C | 222 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

