CHAMPION ANH CA GREASE EP 3

This lithium-free multipurpose grease is an anhydrous calcium (ANH Ca) thickened lubricating grease based on a mineral oil.

The grease contains antioxidants, corrosion inhibitors and EP/AW additives.

APPLICATIONS

The ANH Ca thickener, together with the special base oil blend, makes this grease suitable for the lubrication of medium loaded bearings and in wet and corrosive environments. This lubricating grease has excellent adhesion and water resistance.

FEATURES

Corrosion protection: very good corrosion protection. Multi-applicability: wide range of use. Water resistance: excellent resistance against water washout.

SPECIFICATIONS

DIN	51502	DIN	КРЗК-20
ISO	12924	ISO	L-XB(F)CIB3

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Texture	Visual		SMOOTH
Colour	VISUAL		Yellow Brown
NLGI Classification	ASTM D217		3
Worked Penetration (60 strokes)	ISO 2137	0.1 mm	220-250
Dropping point	ISO 2176/IP 396	°C	> 140
Four Ball Weld Load	ASTM D2596/ DIN51350:4	Ν	3000
Base Oil Viscosity at 40 °C	ASTM D7152	cSt	110

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV G. Gilliotstraat 52 – 2620 Hemiksem – Belgium Tel. +32 3 870 00 00 www.championlubes.com

