

CHAMPION **ECO FLOW** 0W20 SP/RC G6 FE

Thanks to its low viscosity and outstanding fluidity this oil significantly reduces wear and ensures fuel savings and lower CO₂ emissions. Optimized additive package reduces soot and deposits and keeps the engine clean. It is suitable for hybrid cars when the OEM specifications are met.

APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest ILSAC GF-6 A standard where fuel economy and CO₂ reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

FEATURES

Total engine protection: performance in keeping the engine clean.

Fuel economy: superior fuel economy and CO₂ reduction.

Cold start: excellent fluidity at low temperature.

SPECIFICATIONS

API	approval SN Plus	FORD	WSS-M2C947-A
API	SN/RC	GM	dexos1™ Gen 2
CHRYSLER	MS 6395	ILSAC	GF-5
FIAT	9.55535-CR1	ILSAC	approval GF-6 A
FIAT	9.55535-GSX	API	SP
FORD	WSS-M2C945-A	API	approval SP/RC
FORD	WSS-M2C946-A	FORD	WSS-M2C962-A

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	42.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.27
Viscosity index	ASTM D2270		175
B.N. [HClO ₄ method]	ASTM D2896	mg KOH/g	8.5
Pour point	ASTM D6892	°C	-48
Flash Point COC	ASTM D92	°C	224

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

