

CHAMPION OEM SPECIFIC

75W90 MV

This is a full synthetic lubricant based on carefully selected very high quality base oils. Due to its specifically selected composition it avoids gear squawk and prolongs the lifetime of the gear lubricant. It noticeably improves low temperature gear shifts and ensures an easy gear change at high temperature.

APPLICATIONS

This product is specifically formulated for gearboxes with integrated differentials of front-wheel driven cars. It has a wide range of OEM transmission applications.

FEATURES

Frictional properties: very smooth gear shifting, no vibration.
Anti-wear protection: significantly extended transmission life.
Extended oil life: excellent thermal and oxidation stability.

SPECIFICATIONS

API	GL-4 +	VW	G 052 145
BMW	MTF LT-4	VW	G 052 190
FORD	ESD-M2C186-A	VW	G 50
FORD	WSD-M2C200-C	VW	G 51
FORD	WSD-M2C200-D	VW	G 052 157
VOLVO	97310	VW	G 005 100
VW	501 50	FORD	SQM-2C9008-A
VW	G 005 000	FORD	ESD-M2C175
VW	G 052 911	OPEL	B 040 1043
MITSUBISHI	.	MB	235.72

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.878
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	94.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	16.17
Viscosity index	ASTM D2270		185
Pour point	ASTM D6892	°C	-42
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	65600
Flash Point COC	ASTM D92	°C	210

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

