

CHAMPION **ECO FLOW** MULTI VEHICLE ATF FE

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions with a high viscosity index, excellent oxidation stability, excellent friction and anti-wear properties providing excellent fuel economy and meeting the requirements of most American, Japanese and European manufacturers.

APPLICATIONS

Its versatile nature guarantees it can be used in the latest generations of automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs.

FEATURES

Frictional properties: very smooth gear shifting, no vibration

Anti-wear protection: significantly extended transmission life

Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

VW	G 055 540	FORD	MERCON LV
CHRYSLER	68157995AA	HYUNDAI	NWS-9638 T5
VW	G 055 162	FORD	MERCON SP
BMW	M-1375.4	BMW	83222152426
NISSAN	MATIC-S	AIISIN-WARNER	AW-1
TOYOTA	AUTO FLUID WS	GM	DEXRON HP
JAGUAR	02JDE26444	ALLISON	C4
HONDA	DW-1	BMW	83222167718
FIAT	9.55550-AV2	ISUZU	WSI
LAND ROVER	LR023288	TESLA	ATF9/EDF2
FORD	WSS-M2C924-A	AIISIN-WARNER	AW-2
VW	G 060 162	FORD	WSS-M2C938-A
VW	G 055 005	FORD	WSS-M2C195-A
HYUNDAI	SP-IV	MB	236.41
MAZDA	FZ	GM	DEXRON VI
HYUNDAI	SPH-IV	BMW	L 12108
FIAT	9.55550-AV5	BMW	83 22 0 397 114
MITSUBISHI	ATF J3	BMW	83 22 9 407 858
MB	236.12	BMW	83 22 2 305 397
AIISIN-WARNER	JWS 3324	BMW	ATF 3

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com





TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm²/s	31.2
Kinematic viscosity at 100°C	ASTM D445	mm²/s	6.2
Viscosity index	ASTM D2270		152
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

