

Product Specification

COATF2

Semi-Synthetic Transmission Fluid

1 L	4 L	5 L	20 L	60 L	200L
COATF2-1	COATF2-4	COATF2-5	COATF2-20	COATF2-60	COATF2-200

LEVELS OF QUALITY

The lubricant COATF2 complies with the following international specifications:

ALLISON C-4; CAT TO-2; FORD MERCON V; GM DEXRON IID; MAN 339D; MB 236.1, 236.7; FORD MERCON M2C 138CJ; VOITH 55.6335.32 (G607); ZF TE-ML 02F, 03D, 04D, 09A, 11A, 11B, 14A, 17C

DESCRIPTION

COATF2 is a lubricant recommended for automatic transmissions, power steering, hydraulically assisted steering and torque converters, whenever it is required a DEXRON IID product. It is also used as a hydraulic oil covering a large temperature range for applications in the automotive, industry and marine field.

APPLICATIONS

It ensures excellent performances in terms of:

- Frictional properties,
- Thermal-oxidative stability,
- Wear and corrosion resistance.

Thanks to the above-mentioned typical features it also ensures both a low pour point and a reduced foaming tendency

Density at 15°C.Kg/dm ³	ASTM D1298	0.860
Colour		Red
Viscosity at 100°C.cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	140
Flammability V.A.°C	ASTM D92	195
Pour Point °C	ASTM D97	-27

The above-mentioned values are indicative of production average values and are not an integral part of the specification.

TDS Comline ATF2_REV.3 October 2021