

## MO5W-30C4

### Fully Synthetic C4 Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
MO5W30C4-1	MO5W30C4-4	MO5W30C4-5	MO5W30C4-20	MO5W30C4-60	MO5W30C4-200

## PRODUCT SPECIFICATION

### DESCRIPTION

**MO5W-30C4** is a 100% synthetic lubricant with low ash content (Low SAPS) produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations.

The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged. It is especially recommended for vehicles of Renault and Daimler groups (MB, Smart). It is recommended to always observe the oil change interval as suggested by the car manufacturer.

### LEVELS OF QUALITY

The lubricant **MO5W-30C4** complies with the following international specifications:

ACEA C4  
API SN, CF  
BMW LL-04  
MB 229.51, 226.51  
RENAULT RN0720

SAE Scale		5W/30
Density at 15°C.Kg/dm <sup>3</sup>	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	12
Viscosity Index	ASTM D2270	160
Flammability V.A.°C	ASTM D92	210
Pour Point °C	ASTM D97	-39
S.A.	ASTM D874	0.49
T.B.N.	ASTM D2896	6

The above-mentioned values are indicative of production average values and are not an integral part of the specification.