

## MODOT5.1

### Fully Synthetic Brake Fluid

1 L	4 L	5 L	20 L	60 L	200L
MODOT51-1	MODOT51-4	MODOT51-5	MODOT51-20	MODOT51-60	MODOT51-200

## PRODUCT SPECIFICATION

### DESCRIPTION

SUPER BRAKE FLUID **MODOT5.1** is a non-silicone fluid based on glycols at a very high boiling point. It has been specifically designed for high-performance hydraulic circuits which apply disc brakes or brake-shoes installed on high performance cars and motorbikes. It is suitable for the use in all braking systems, whenever it is required a fluid at DOT5.1 level.

**MODOT5.1** may be used as a top-up in systems designed for a fluid at DOT4 level. Furthermore, it is compatible with all glycol-based brake fluids. It ensures the maximum protection against the vapour lock phenomenon, that it is to say the formation of vapour bubbles which impairs the quality of brakes.

### LEVELS OF QUALITY

The lubricant **MODOT5.1** complies with the following international specifications:

SAE J1703

FMVSS 116 DOT4, DOT5.1

ISO 4925

Recommended for VW, AUDI, FERRARI, MASERATI

Properties		Values
Specific weight at 20°C	ASTM D1298	1030
Colour	VISUAL	Straw Yellow
Flammability V.A.°C	ASTM D92	100
Boiling point T.Q.		280
Boiling point after humidification		175
Viscosity at 40°C	ASTM D445	lower than 90
Viscosity at 100°C	ASTM D445	higher than 2
pH		9 up 11.5

The above-mentioned values are indicative of production average values and are not an integral part of the specification.