



Product info sheet

VDO

A2C59511600

Special tools needed?

No

| |
|--|
| |
|--|

| |
|--|
| |
|--|

Product specific information

Programming

No

| |
|--|
| |
|--|

Unlocking

No

| |
|--|
| |
|--|

Adaption values reset

No

| |
|--|
| |
|--|

Bleed

Yes

Ignition for 30 s, bleedscrew open.

adjustment at mounting_1

No

| |
|--|
| |
|--|

| |
|--|
| |
|--|

| |
|--|
| |
|--|

adjustment at mounting_2

| |
|--|
| |
|--|

| |
|--|
| |
|--|

| |
|--|
| |
|--|

Tightening torques

Mounting fuelpump flange

1: 20 Nm, 2: 25 Nm

| |
|--|
| |
|--|

| |
|--|
| |
|--|

| |
|--|
| |
|--|

| |
|--|
| |
|--|

| |
|--|
| |
|--|

Assembly instructions

Recommendation: replace fuel filter

Recommendation: replace drive plate

Core charge terms:

- externally intact,
- no mechanical damage,
- not dismantled,
- no heavy corrosion.

| |
|--|
| |
|--|

| |
|--|
| |
|--|

| |
|--|
| |
|--|

| |
|--|
| |
|--|