according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl Uni GL-4/5 75W-90

Version: 1 Latest revision: Date of issue: 10. 11. 2017 Page: 1/(12)

SECTION 1 Identification of the mixture/substance and of the company/undertaking

1.1 Product identifier:

A.Z. Meisterteile Getriebeöl Uni GL-4/5 75W-90

1.2 Relevant identified uses of the <u>mixture</u> or substance and uses advised against

Relevant identified uses: semi-synthetic multigrade gear oil

Uses advised against: no data

1.3 Details of the supplier of the safety data sheet:

Trader identification: Technical information:

UNIX Autó és Alkatrészkereskedelmi Kft. UNIX Autó és Alkatrészkereskedelmi Kft.

H-1139 Budapest, Frangepán u. 55-57. H-1139 Budapest, Frangepán u. 55-57.

Tel.: 06 1 270 8700 Tel.: 06 1 270 8700 Fax: 06 1 270 8799 Fax: 06 1 270 8799

E-mail: info@unixauto.hu E-mail: info@unixauto.hu

Responsible for SDS:

UNIX Autó és Alkatrészkereskedelmi Kft.

H-1139 Budapest, Frangepán u. 55-57.

Tel.: 06 1 270 8700 Fax: 06 1 270 8799

E-mail: info@unixauto.hu

1.4 Emergency telephone number

Emergency telephone (07-15²⁰ h): +36 34 526 210 (CET) on workdays

Health Toxicological Information Service (ETTSZ 1096 Budapest, Nagyvárad tér 2.)

Tel.: 36 80 201 199 (0-24 h, free number).

SECTION 2 Hazards identification

2.1 Classification of the <u>mixture</u> or substance

Hazard Class and Category: Hazard statement:

Not classified.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl Uni GL-4/5 75W-90

Version: 1 Latest revision: Date of issue: 10. 11. 2017 Page: 2/(12)

2.2 Label elements

Product identification: Trade name: A.Z. Meisterteile Getriebeöl Uni GL-4/5 75W-90

Hazardous component(s): -

GHS Pictogram: Not required. Signal word: Not required.

Hazard statement: **Not required.**

Supplemental hazard information:

EUH208 Contains Long-chain alkyl amine. May produce an allergic reaction.

Precautionary statements – General: -

Precautionary statements – Prevention:

P273 Avoid release to the environment.

Precautionary statements – Response: -

Precautionary statements – Storage: -

Precautionary statements – Disposal:

P501 Dispose of contents/container in accordance with national regulation.

Other liabilities for labelling:

Tactile warning of danger: Not required.

Transport classification: see section 14.

2.3 Other hazards

The product does not contain any PBT or vPvB substance according to annex XIII of regulation (EC) 1907/2006.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl Uni GL-4/5 75W-90

Version: 1 Latest revision: Date of issue: 10. 11. 2017 Page: 3/(12)

SECTION 3 Composition/information on ingredients

3.2 Mixtures

Chemical description: Mixture of refined mineral and synthetic oils containing additives.

Component(s) / Hazardous component(s):

Name	EU	CAS	Hazard classes and	Hazard	Conc.
Ivaille	number	number	cat.	statements	%(m/m)
Base oil – unspecified, hydrotreated heavy paraffinic, C20-C50* REACH Registr. Nr.:	265-157-1	64742-54-7	Asp.Tox.1 (Note L)	H304	max. 50
01-2119484622-25 Base oil – unspecified, hydrotreated heavy paraffinic, C20-C50* REACH Registr. Nr.: 01-2119484622-25	265-157-1	64742-54-7	- (Note L)	-	max. 50
Base oil – unspecified, hydrotreated neutral oil- based, C20-C50*	276-738-4	72623-87-1	Asp.Tox.1 (Note L)	H304	max. 35
1-Decene Homopolymer, Hydrogenated REACH Registr. Nr.: 01-2119486452-34	500-183-1	68037-01-4	-	-	max. 35
Lubricating oils (petroleum), C>25* REACH Registr. Nr.: 01-2119486948-13	309-874-0	101316-69-2	(Note L)	-	max. 10
Mineral oil raffinate*		confidential	- (Note L)		max. 5
Long-chain alkyl amine		confidential	Acute Tox. 4 Acute Tox. 3 Skin Sens. 1 Aquatic Acute 1 Aquatic Chronic 1	H302 H311 H317 H400 H410	max. 0.2
Long-chain alkenyl amine		confidential	Acute Tox. 4 Skin Corr. 1A Aquatic Acute 1	H302 H314 H400	max. 0.2

^{*:} with exposure limit

The full text of each relevant H- phrase and Hazard classes and cat. see in Section 16.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl Uni GL-4/5 75W-90

Version: 1 Latest revision: Date of issue: 10. 11. 2017 Page: 4/(12)

SECTION 4 First aid measures

4.1 Description of first aid measures

General information: Never give anything by mouth to an unconscious person, or never

induce vomiting.

Inhalation: Remove the affected person to fresh air. If rapid recovery does not occur, obtain

medical attention.

Skin contact: Remove contaminated clothing. Wash skin with large amounts of water, use

soap. In case of persistent irritation, get medical attention.

Eye contact: Flush eyes with plenty of water for 10-15 minutes. In case of persistent

irritation, get medical attention.

Ingestion: If swallowed, give water. Do not induce vomiting. Get medical attention.

Protection of first-aid person: No individual specifications.

4.2 Most important symptoms and effects, both acute and delayed

Prolonged and/or repeated contact may cause irritation on skin depending on individual sensitivity.

4.3 Indication of any immediate medical attention and special treatment need Not required.

SECTION 5 Fire-fighting measures

Fire hazards:

Combustible

5.1 Extinguishing media

Suitable extinguishing media:

Foam, carbon dioxide, dry chemical powder.

Unsuitable extinguishing media:

Water jet.

5.2 Special hazards arising from the mixture or substance

Hazardous combustion products:

On burning, carbon monoxide, carbon dioxide, various hydrocarbons and soot can be formed.

5.3 Advice for fire-fighters

Special protective equipment:

According to the existing fire-fighting regulations.

Further information:

-

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl Uni GL-4/5 75W-90

Version: 1 Latest revision: Date of issue: 10. 11. 2017 Page: 5/(12)

SECTION 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Personal precautions: see Section 8.

6.2 Environmental precautions:

Confine spills to prevent material from entering sewers, watercourses, drains and into soil Notify relevant authority.

6.3 Methods and material for containment and cleaning up

On soil: All kind of ignition sources should be remove. Contain spilled liquid with

sand, earth or other suitable absorbents. Recover free liquid by pumping.

Dispose of according to local regulations.

On water: Confine the spillage. Remove from surface by skimming or suitable

absorbents. Notify local authorities according to regulations.

6.4 Reference to other sections

Personal precautions: see section 8.

Waste treatment methods: see section 13.

SECTION 7 Handling and storage

7.1 Precautions for safe handling

Keep general measures applied for normal operations with lubricants.

Keep away from radiant heat and open flame.

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or mists.

Ensure washing facilities after working hours and before breaks. Take off contaminated or oil-soaked clothing, wash with warm water and soap.

When using do not eat, drink or smoke. Avoid splashing the product.

Handling temperature: not known

7.2 Conditions for safe storage, including any incompatibilities

Storage facilities must comply with regulations for storing of flammable liquids.

Store in dry, well ventilated place in original, closed containers.

Keep away from radiant heat, open flame and strong oxidizing agents.

Storage temperature: max. 40°C

7.3 Specific end use(s)

Semi-synthetic multigrade gear oil.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl Uni GL-4/5 75W-90

Version: 1 Latest revision: Date of issue: 10. 11. 2017 Page: 6/(12)

SECTION 8 Exposure controls / personal protection

Engineering control measures:

Not required.

8.1 Control parameters:

Mineral oil mist: TWA: 5 mg/m³; STEL: 10 mg/m³, for oil mist, vapour excluded

(ACGIH).

Method of testing, recommended: NIOSH 5026

8.2 Exposure controls

Personal protection:

Respiratory protection: Breathing apparatus not required.

Hand protection: Oil resistant gloves (EN 374, Breakthrough time 480 min) (e.g.

nitrile rubber – minimal thickness 0.33 mm).

Note: Manufacturer's directions for use and the conditions of

application should be observed.

Eye protection: Protective goggles (EN 166).
Skin protection: Protective clothing (oil resistant).

Other special: No data.

Environmental exposure controls:

Do not discharge into drains/surface waters/groundwater.

SECTION 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:

Physical state: liquid

Colour: yellow, clear Odour: characteristic

Change in physical state:

Pour point (ISO 3016): typ. -42°C Boiling point (DIN 51356): not available

Others:

Flash point (COC) (EN ISO 2592): typ. 215°C Ignition point (EN ISO 2592): not available Autoignition temperature: not available Explosive properties: not explosive Oxidizing properties: not oxidize Vapour pressure at 20°C: negligible

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl Uni GL-4/5 75W-90

Version: 1 Latest revision: Date of issue: 10. 11. 2017 Page: 7/(12)

Density at 15°C (EN ISO 12185): 0.800 - 0.880 g/cm³

Solubility in water: practically insoluble in water gasoline, kerosene, toluene, etc.

n-Octanol/water partition coefficient:

Vapour density:

Kinematic viscosity at 40°C (EN ISO 3104):

Kinematic viscosity at 100°C (EN ISO 3104):

typ. 109.3 mm²/s

typ. 15.3 mm²/s

pH: oot applicable

9.2 Other information

no data available

SECTION 10 Stability and reactivity

10.1 Reactivity: Dangerous reactivity not known.

10.2 Chemical stability: No decomposition if stored and handled properly.

10.3 Possibility of hazardous

reactions: Not known

10.4 Conditions to avoid: Direct heat or ignition sources.

10.5 Incompatible materials: Strong oxidizing agents.

10.6 Hazardous decomposition No dangerous decomposition products are formed under normal

products: conditions. Hazardous combustion products: See Section 5.

SECTION 11 Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

Oral: Dermal:

Acute toxicity: irritation

Skin: not irritant (based on components)

Eye: not irritant (based on components), causes serious eye irritation.

Note: Prolonged and/or repeated contact may cause irritation on skin depending on

individual sensitivity. May cause dermatitis.

If vapours are generated from heating, exposure may cause irritation of

mucous membranes and the upper respiratory tract.

Respiratory or skin sensitisation: not sensitising (based on components)

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



A.Z. Meisterteile Getriebeöl Uni GL-4/5 75W-90 Trade name:

Version: 1 Latest revision: Date of issue: 10, 11, 2017 Page: 8/(12)

Other information, specific effects:

The product does not contain PCBs, PCTs, and other chlorine compounds, and heavy metals, barium compounds.

NOTE L: The base oil(s) contain(s) less than 3% DMSO extract (IP 346), therefore not classified as carcinogenic material according to 1272/2008/EC.

Germ cell mutagenicity: not known, resp. not mutagen (based on components) Carcinogenicity: not known, resp. not carcinogen (based on components) Reproductive toxicity: not known, resp. no reproduction-damaging effect

(based on components)

STOT-single exposure: not classified STOT-repeated exposure: not classified Aspiration hazard: not classified

SECTION 12 Ecological information

12.1 Toxicity Not available.

> Aquatic organisms: Soil organisms:

Plants:

12.2 Persistence and degradability No data available. Biodegradability: No data available. 12.3 Bioaccumulative potential No data available.

12.4 Mobility

Mobility in soil: Absorbs in soil. Mobility in water: Floats on water.

12.5 Results of PBT and vPvB

assessment Does not contain PBT and vPvB substances.

12.6 Other adverse effects

Heavy metal content: None.

PCT, PCB and other chlorinated

hydrocarbons: None.

Spills may form a film on water surfaces causing Environmental effects:

impaired oxygen transfer.

Water hazard class (German): WGK 1 (Classification by VwVwS)

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl Uni GL-4/5 75W-90

Version: 1 Latest revision: Date of issue: 10. 11. 2017 Page: 9/(12)

SECTION 13 Disposal considerations

13.1 Waste treatment methods

Product disposal:

Wastes of the product or used oil should be treated as hazardous waste.

Waste Identification Code: 13 02 06* Synthetic engine, gear and lubricating oils.

Waste Identification Code: 13 02 05*

Mineral-based non-chlorinated engine, gear and lubricating oils. Disposal must be in compliance with national and local regulations.

Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

Waste Identification Code: 15 01 10*

packaging containing residues of or contaminated by dangerous substances

Disposal must be in compliance with national and local regulations.

Recommended waste treatment method: incineration

Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

Care should be taken in any case to ensure compliance with EC, national and local regulations. It is the responsibility of the user to know all relevant national and local regulations.

SECTION 14 Transport information

Land transport:

Road/ Railway ADR/RID: Not classified.

14.1. UN number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards:

14.6. Special precautions for user:

Waterways:

Inland waterways/ Sea transport ADN/IMDG: Not apply to the product.

Air transport: ICAO / IATA: Not apply to the product.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl Uni GL-4/5 75W-90

Version: 1 Latest revision: Date of issue: 10. 11. 2017 Page: 10/(12)

SECTION 15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the mixture. This safety data sheet has been prepared according to Regulation (EC) No 1907/2006 (mod.: 2015/830/EU) and to Regulation (EC) 1272/2008.
- 15.2 Chemical safety assessment. not available

SECTION 16 Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use. The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.

Source of data presented in this material safety data sheet:

Test results of this product

Material safety data sheets of product's components

Hungarian and EU lists of dangerous substances

Relevant Hungarian regulation and EU directives

Classification for mixtures and used evaluation method according to regulation 1272/2008/EC (CLP)

Not classified.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl Uni GL-4/5 75W-90

Version: 1 Latest revision: Date of issue: 10. 11. 2017 Page: 11/(12)

The full text of each relevant Hazard classes and cat., H- phrase in Section 3.:

H302 Harmful if swallowed

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Acute Tox. 4 Acute toxicity Category 4
Asp. Tox. 1 Aspiration hazard Category 1
Acute Tox. 3 Acute toxicity Category 3

Skin Corr. 1A Skin corrosion/irritation Category 1A Skin Sens. 1 Respiratory/skin sensitization 1 Category

Aquatic Acute 1 Hazardous to the aquatic environment, Acute Category
Aquatic Chronic 1 Hazardous to the aquatic environment, Chronic Category 1

Legend:

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE Acute Toxicity Estimate
BCF Biocontrentration Factor
BOD Biological Oxigen Demand

Bw Body Weight

C&L Classification and Labeling CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

CMR Carcigonic, Mutagenic or toxic to Reproduction

COD Chemical Oxygen Demand
CSA Chemical Safety Assessment
CSR Chemical Safety Report
DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
ECHA European Cheamicals Agency
Ecx Effective Concentration x%

Edx Effective Dose x%

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl Uni GL-4/5 75W-90

Version: 1 Latest revision: Date of issue: 10. 11. 2017 Page: 12/(12)

ELINCS	European List of Notified Chemical Substances
ErC50	EC50 in terms of reduction of growth rate;
ES	Exposure Scenario
ESIS	European Chemical Substances Information System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LCx	Lethal Concentration x%
LDx	Lethal Dose x%
LOAEC	Lowest Observed Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
NOEC	No observed effect concentration
NOEL	No observed effect level
NLP	
	No-Longer Polymer No Observed Adverse Effect Level
NOAEL	
OECD	Organisation for Economic Cooperation and Development
PBT	Persistent Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SVHC	Substance of Very High Concern
UVCB	substance of unknown or variable composition, complex reaction products or biological
***	materials
VOC	Volatile organic compounds

Revision Indicators:

vPvB

Section	Subject of change	Date	Version

Very Persistent and very Bio-accumulative