

한국앤컴퍼니 주식회사


286, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13494 Korea


> Type No.: MF54080 Created: 05.02.2022 Modified: 05.02.2022

TECHNICAL DATA SHEET









PERFORMANCE				CONTAINER		
VOLTAGE:	12	V	Group:	LO	Black	
C20:	40	Ah	Hold Down:	B13		
CCA:	340	EN	Please refer to the cat	calog or our website for the deta	ails of hold down	
Vibration:	V3		types of the battery co	types of the battery container.		
Endurance:	-		COVER			
Water consumption:	W4		Type:	Heat sealed	Black	
Technology:	Flooded		Polarity:	L		
Grid alloy:	Ca/Ca		Terminals:	Standard		
			Filter:	2 Filters both sides		
WEIGHT AND STD. DIMENSION				HANDLES		
Battery weight:	10,7	kg	Handles:	N/A		
Volume acid:	2,8	1		REMARK		
Length:	174	mm				
Width:	174	mm				
Height:	190	mm				
Total Height:	190	mm				

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by HANKOOK & COMPANY.