

## Hankook & Company

한국앤컴퍼니 주식회사 286, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13494 Korea


**TECHNICAL DATA SHEET** 

Type No.: MF57413 Created : 05.02.2022 Modified : 05.02.2022





F	G	and the second	the second second	Ð	
4					à
	V	- V		V	



PE	RFORMANCE			CONTAINER					
VOLTAGE:	12	V	Group:	L3	Black				
C20:	74	Ah	Hold Down:	B13					
CCA:	680	EN	Please refer to the cata	log or our website for the det	ails of hold down				
Vibration:	V3		types of the battery cor	types of the battery container.					
Endurance:	-	COVER							
Water consumption:	W4		Type:	Heat sealed	Black				
Technology:	Flooded		Polarity:	R					
Grid alloy:	Ca/Ca		Terminals:	Standard					
			Filter:	2 Filters both sides					
WEIGHT A	ND STD. DIME	NSION		HANDLES					
Battery weight:	17,1	kg	Handles:	1 handle					
Volume acid:	4,2	I.		REMARK					
Length:	277	mm							
Width:	174	mm							
Height:	190	mm							
Total Height:	190	mm							
This document includes confidential data is not contractual and could be changed without notice. Any use convior distribution has to be authorised in									

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by HANKOOK & COMPANY.