
## Hankook & Company


## 한국앤컴퍼니 주식회사


286, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13494 Korea


> Type No.: AGM L3 Created: 05.02.2022 Modified: 05.02.2022

## **TECHNICAL DATA SHEET**









PERFORMANCE			CONTAINER		
VOLTAGE(V):	12	V	Group:	L3	Black
C20(Ah):	70	Ah	Hold Down:	B13	
RC(min):	140	min	Please refer to the catal	og or our website for the deta	ails of hold down
CCA(A):	680	EN	types of the battery container.		
Vibration:	V3		COVER		
Endurance:	E4		Type:	6-valved cap	Black
Water consumption:	W5		Polarity:	L	
Technology:	VRLA		Terminals:	Standard	
Grid alloy:	Ca/Ca		Filter:	2 Filters both sides	
WEIGHT AND STD. DIMENSION			HANDLES		
Battery weight(kg):	20,50		Handles:	2 handles	
Volume acid(l):	3,57			REMARK	
Length(mm):	277				
Width(mm):	174				
Height(mm):	190				
Total Height(mm):	190				

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by HANKOOK & COMPANY.