

Hankook & Company


한국앤컴퍼니 주식회사 286, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13494 Korea


TECHNICAL DATA SHEET

Type No.: AGM M31-925 Created : 05.02.2022 Modified : 05.02.2022









PERFORMANCE			CONTAINER		
VOLTAGE(V):	12	V	Group:	31	Black
C20(Ah):	100	Ah	Hold Down:	BO	
RC(min):	200	min	Please refer to the catalog or our website for the details of hold down		
CCA(A):	925	EN	types of the battery container.		
Vibration:	V3		COVER		
Endurance:	E4		Type:	6-valved cap	Black
Water consumption:	W5		Polarity:	R	
Technology:	VRLA		Terminals:	MARINE TWIN*	
Grid alloy:	Ca/Ca		Filter:	2 Filters both sides	
WEIGHT AND STD. DIMENSION			HANDLES		
Battery weight(kg):	27,20		Handles:	1 Handle	
Volume acid(l):	4,87			REMARK	
Length(mm):	332				
Width(mm):	172				
Height(mm):	231				
Total Height(mm):	231				
This document includes confi					

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by HANKOOK & COMPANY.