



# ACDelco

## SELECT 15W-40 ENGINE OIL

### ENGINEERED FOR PERFORMANCE



### PRODUCT DESCRIPTION

ACDelco Select 15W-40 is a premium mineral engine oil, designed to provide a high level of protection and performance for naturally aspirated and turbo charged petrol & diesel engines. It is also suitable for use in LPG and E10 fueled engines.

### FEATURES & BENEFITS

- Very high resistance against oxidation
- High detergent and dispersant properties
- High performance in high and low temperature conditions.
- Excellent protection against wear
- Low loss by evaporation
- Broad application field

### APPLICATIONS

ACDelco Select 15W-40 is formulated to be suitable for in many vehicles, particularly the following vehicle types and conditions:

- mixed fleet
- Latest engine technologies
- Highway cruising
- Normal operating conditions

Look out for the application symbols across the ACDelco engine oil range. These will help you quickly find the spec you need.



For your nearest ACDelco Automotive Parts Stockist  
call **1800 ACDelco** or visit **acdelco.com.au**

# ACDelco

# ACDelco

## SELECT 15W-40 ENGINE OIL



### ENGINEERED FOR PERFORMANCE



#### PROPERTIES AND SPECIFICATIONS

Recommended for use in applications requiring:

API SN Plus, SN, SM, SL, SJ / CF, ACEA A3/B3

##### Properties

- Grade SAE 15W-40
- Kinematic Viscosity @ 100 °C, 14.5 mm<sup>2</sup>/s, ASTM D445
- Kinematic Viscosity @ 40 °C, 104 mm<sup>2</sup>/s, ASTM D445
- Viscosity Index, ASTM D2270 143
- Density @ 15.6 °C, 0.873 g/ml, ASTM D4052
- Pour Point, -39°C, ASTM D97
- Flash Point, Cleveland Open Cup, 239 °C, ASTM D92
- Ash, Sulfated, 0.9 mass%, ASTM D874
- Total Base Number, 10 mgKOH/g, ASTM D2896
- Mini-Rotary Viscometer, Apparent Viscosity, -25 °C, mPa.s, ASTM D4684 14600
- Hi-Temp Hi-Shear Viscosity @ 150 °C 1x10(6) sec(-1), mPa.s, ASTM D4683 3.9

#### HEALTH & SAFETY

Material Safety Data Sheets (MSDS) are available for download at [www.acdelco.com.au](http://www.acdelco.com.au)

This product should not be used for purposes other than its intended use.

If disposing of used product, take care to protect the environment.



ACDelco P/N	Size (L)
19375071	5
19375072	20
19375073	208



For your nearest ACDelco Automotive Parts Stockist  
call **1800 ACDelco** or visit **[acdelco.com.au](http://acdelco.com.au)**

**ACDelco**