



TECHNICAL DATA SHEET

GM 5W-30 LL

Product Type 5W-30 SYNTHETIC MOTOR OIL
Product Code N232

Description

A high performance synthetic engine oil suitable for use in a wide variety of modern petrol and diesel engines.

Benefits

- Suitable for a wide range of vehicles
- Allows for extended drain capability
- Not to be used in vehicles with diesel particulate filters

Specifications

Always check the owner's manual for the correct oil specification to use.

- ACEA A3/B4
- API SM/CF
- BMW LONGLIFE-01
- GM LL-A-025, LL-B-025
- MERCEDES-BENZ MB-229.5
- VOLKSWAGEN 502 00/505 00





TECHNICAL DATA SHEET

GM 5W-30 LL

Product Type 5W-30 SYNTHETIC MOTOR OIL
Product Code N232

Typical Properties

SAE Viscosity Grade	SAE J300	-	5W-30
Viscosity @ 100°C	ASTM D-445	mm ² /s	12,3
Viscosity @ 40°C	ASTM D-445	mm ² /s	73
Viscosity Index	ASTM D-2270	-	167,0
Viscosity @-25°C	ASTM D-5293	mPa.s	6060,0
Total Base Number	ASTM D-2896	mg/KOH/g	12
Pour Point	ASTM D-5949	°C	-36
Specific Gravity @15.6°C	ASTM D-4052	-	1
Flash Point (COC)	ASTM D-92	°C	226

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Eskan Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDON

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu