



TECHNICAL DATA SHEET

CLASSIC-FLEET HD 30

Product Type 30 MINERAL MOTOR OIL
Product Code NT111

Description

Suitable for normally aspirated diesel and petrol engines in passenger cars, light commercials, plant, compressor, industrial and certain hydraulic and transmission applications.

Benefits

- Cost effective
- Suitable for mixed fleet viscosities
- Available in varying viscosities

Specifications

Always check the owner's manual for the correct oil specification to use.

- API CC/SE
- CCMC D1
- MIL-L-2104B
- MIL-L-46152B



TECHNICAL DATA SHEET

CLASSIC-FLEET HD 30

Product Type 30 MINERAL MOTOR OIL
Product Code NT111

Typical Properties

SAE Viscosity Grade	SAE J300	-	30,0
Viscosity @ 100°C	ASTM D-445	mm ² /s	10,5
Viscosity @ 40°C	ASTM D-445	mm ² /s	73
Viscosity Index	ASTM D-2270	-	129,0
Viscosity @-20°C	ASTM D-5293	mPa.s	0,0
Total Base Number	ASTM D-2896	mg/KOH/g	7
Pour Point	ASTM D-5949	°C	-36
Specific Gravity @15.6°C	ASTM D-4052	-	1
Flash Point (COC)	ASTM D-92	°C	242

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Eskan Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDON

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu