



TECHNICAL DATA SHEET

SM 85W-140 GL5

Product Type	85W-140 MINERAL GEAR OIL
Product Code	NT318

Description

Recommended for highly stressed manual gearboxes, heavily loaded axle drives and synchronised or non-synchronised transmissions where an oil meeting the approvals of this grade is called for

Benefits

- Excellent corrosion protection
- Superior seal compatibility
- Fully compatible with synchromesh transmissions
- Outstanding thermal stability
- Longer oil drain capability

Specifications

Always check the owner's manual for the correct oil specification to use.

- API GL-5, MT-1
- MACK GO-J
- MILITARY MIL-PRF-2105E
- SAE J2360
- SCANIA STO 1:0
- ZF TE-ML 05A, 07A, 08, 12M, 16B, 16C, 16D, 17B & 21A,



TECHNICAL DATA SHEET

SM 85W-140 GL5

Product Type 85W-140 MINERAL GEAR OIL
Product Code NT318

Typical Properties

Test	Method	Unit	Value
SAE Viscosity Grade	SAE J306	-	85W-140
Viscosity @ 100°C	ASTM D-445	mm ² /s	13,5
Viscosity, @ 40°C	ASTM D-445	mm ² /s	119,0
Viscosity Index	ASTM D-2270	-	111
Viscosity @ -12°C	ASTM D2983	mPa.s	15000
Pourpoint	ASTM D5949	°C	-24
Specific gravity	ASTM D-4053	-	0,873
Flash point	ASTM D-93	°C	210

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

DEVELOPED BY VALVOLINE™



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Esplan Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDOM

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu