

2 COLUMNS POST LIFT 400V 6T HIGH PASSAGE 5080mm 2.6Kw

Reference : PE 2012T



Item name	2 COLUMNS POST LIFT 400V 6T HIGH PASSAGE 5080mm 2.6Kw
EAN code	3701555307053
Intro	Particularly adapted to repair activities on extended utility vehicles, 4x4, micro car.
Text	Electro-hydraulic post lift. Hoses and cables pass through the top for optimal working comfort, allowing free access under the vehicle for equipment (jacks, oil recuperator...), making it easier to clean the workshop. Hydraulic unit: quick up and down with adjustment possibility, equipped with a position securing device for precise intervention, gearbox assembly, nut alignment... Multiple lifting capacities thanks to the articulated arms in symmetrical version (3 stages from 790 to 1890mm) allowing lifting adjustable to the millimeter of vehicles.
Product highlight	Large scope of application
Specifications	Specifications: - lifting height : 100-1920mm - lifting time : +/- 80s - lowering time : +/- 100s - driving power: 2.6kW - drive voltage: (3 ~) 400/50 V/Hz - concrete strength/quality: 200mm-C20/25 - adjustable buffers on screw 55mm stroke (+ raised 70 and 160mm) - electro-magnetic unlocking of the safety notches - bevelled columns for large door openings

- overload and hose rupture safety
- semi-automatic hydraulic system synchronization
- made in Europe
- epoxy paint

Options

Options :
- PE0007: Mercedes/Iveco 105-135mm extension sets

Advice

Installation et mise en service, nous consulter.
Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.
Frais de transport non inclus.

Warranty period 2 years

Power 2600W

Tension 400V

Product weight 1,370.00 kg

Maximum load (T) 6.00 T

Tariff code Tariff Equipment (TE)

Composition of nomenclature 1 x PE 2012T-1 - 2 COLUMNS POST LIFT 400V 6T HIGH PASSAGE 5080mm 2.6Kw
PACK. 1/1



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to
12h30 and from 14h to 17h30
(16h30 on Friday)