

## 4 COLUMNS POST LIFT 5T AUXILIARY LIFT

Reference : PE 4102T



|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Item name</b>         | 4 COLUMNS POST LIFT 5T AUXILIARY LIFT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>EAN code</b>          | 3701555318097                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Text</b>              | <p>Suitable for mechanical work, light commercial vehicles, camper vans, construction equipment, ideally designed for geometry with manual swash plates and optional turntable slots.</p> <p>5T auxiliary lifts with double galvanized extensions.</p> <p>Suitable for mechanical work, passenger cars, light commercial vehicles, camper vans and construction equipment.</p> <p>Work comfort: access platforms equipped with auxiliary lift.</p> <p>Fast, easy positioning of low-clearance vehicles, for rapid repair or inspection, 5160mm long tracks.</p> <p>Optional parking kit for 2 cars. PE 4103.</p> |
| <b>Product highlight</b> | 5T auxiliary lifts with double galvanized extensions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Specifications</b>    | <p>Specifications:</p> <ul style="list-style-type: none"><li>- lifting height: 220-1850mm</li><li>- lifting time: +/- 50s</li><li>- lowering time: +/- 30s</li><li>- track width/length: 500/5160mm</li><li>- adjustable distance between runways: 910-1010mm</li><li>- required air supply 6-8 bar.</li><li>- drive power: 3kW</li><li>- drive voltage: (3 ~) 400/50 V/Hz</li></ul>                                                                                                                                                                                                                             |

- maximum safety: single-cylinder lifting, synchronization driven by 4 cables
- pneumatic release of safety catches
- auxiliary lifts 5T capacity
- safety system in case of cable breakage,
- emergency lowering system in case of power failure
- intermediate stop at 20 cm from the ground for user safety and anti-crushing audible signal
- air outlet under rails
- engine protection
- 230V power socket on electric box
- pneumatic swashplates
- Epoxy paint

#### Advice

Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.

Frais de transport non inclus.

#### Warranty period

2 years

#### Power

3000W

#### Tension

400V

#### Width

3,185.00 mm

#### Height

2,350.00 mm

#### Max. height

1,850.00 mm

#### Min. height

220.00 mm

#### Drive through width

2,830.00 mm

#### Maximum load (T)

5.00 T

#### Tariff code

Tariff Equipment (TE)

#### Composition of nomenclature

1 x PE 4102T-1 - 4 COLUMNS POST LIFT 5T AUXILIARY LIFT 1/1  
4 x [SA 3012 - HV46 HYDRAULIC OIL 5L](#)

#### Warranty Procedure

INTERVENTION

#### Customer benefit

Supplied with HV46 hydraulic oil and ground fixing kit



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to  
12h30 and from 14h to 17h30  
(16h30 on Friday)