

DESCRIPTION



Supersint GM D1 0W-20

Fuel-economy, High-Performance smooth-running engine oil



1. APPLICATION

Fuel-economy high-performance passenger car engine oil, also specially developed to prevent early ignition (LSPI). Modern GM (Opel) gasoline engines according to **dexos 1™ Gen 3** in turbocharged/non-turbocharged passenger cars/vans and US vehicles to prevent In addition, it has the capability to meet the demanding requirements of modern day to meet hybrid vehicles. Suitable for the longest oil change intervals according to manufacturer specifications.

2. YOUR BENEFIT

- Prevents pre-ignition (LSPI).
- Fuel economy and low exhaust emissions.
- Outstanding engine and especially piston cleanliness.
- Very high viscosity stability and aging resistance.
- Very good protection against wear, corrosion and deposits.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- API SP (RC), API SN Plus (RC)
- ILSAC GF-6A/GF-5
- Acura; Buick; Cadillac; Chrysler MS-6395; Chevrolet
- Dodge; Fiat 9.55535-GSX/-CR1; GMC; Jeep
- GM dexos 1™ Gen 3/GM 6094M
- Ford WWS-M2C962-A/947-A/946-A/945-A



DESCRIPTION



Quality engineered in Germany



Supersint GM D1 0W-20

Fuel-economy, High-Performance smooth-running engine oil

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	843	Kg/m ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	44,2	mm ² /s	ASTM D7279
Kin. Viscosity at 100°C	8,4	mm ² /s	ASTM D7279
Viscosity Index	169		ASTM D2270
Flashpoint	236	°C	DIN ISO 2592
Pourpoint	-48	°C	ASTM D7346

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	123700	20 Liter	123730
205 Liter	123710	4 x 5 Liter	123750
60 Liter	123720	12 x 1 Liter	123770

