

DESCRIPTION

emka®

Quality engineered in Germany

Supersint FE 10W60

Ultra High-Performance engine oil



1. APPLICATION

Supersint FE 10W60 is an ultra high performance engine oil for different car models with and without Service interval extension. Carefully selected, highly effective additives give this engine oil excellent properties.

2. YOUR BENEFIT

- Significant fuel savings possible.
- Excellent protection against corrosion.
- Excellent shear stability behavior prevents viscosity drop.
- Excellent engine cleanliness justified by the modified combination of additives.
- Suitable for extended oil change intervals according to the manufacturer's specifications.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA A3/B4
- API SN, API CF
- BMW M Series; Longlife-01
- Fiat 9.55535-H3
- Mercedes Benz 229.3
- VW 501 01/505 00



DESCRIPTION

emka®

Quality engineered in Germany

Supersint FE 10W60

Ultra High-Performance engine oil



4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	855	Kg/m ³	DIN EN ISO 12185:1997-11
Kin. Viscosity at 40°C	156,0	mm ² /s	DIN 51659-2:2017-02
Kin. Viscosity at 100°C	9,5	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	194		DIN ISO 2909:2004-08
Pourpoint	-30	°C	ASTM D 7346:2015
Flashpoint	235	°C	DIN EN ISO 2592:2018-01
Total Base Number (TBN)	9,5	Mg KOH/g	ASTM D 2896:2015

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0127000	20 Liter	0127030
205 Liter	0127010	4 x 5 Liter	0127050
60 Liter	0127020	12 x 1 Liter	0127075

