

DESCRIPTION

emka®

Quality engineered in Germany

Hypoid SAE 85W90

High-Performance gear oil



1. APPLICATION

Hypoid SAE 85W90 is a high-performance gear oil for heavily loaded axle drives in commercial vehicles and work machines. It offers the fastest possible oil circulation even at very low outside temperatures.

This results in excellent transmission efficiencies and thus lowest power losses.

2. YOUR BENEFIT

- Very high shear stability.
- Excellent wear protection.
- Very good oxidation resistance.
- Very low foaming tendency even at high speeds.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- API GL-5
- Daimler Truck DTFR 12B100 (MB 235.0)
- MAN M 342 Typ M1
- MIL-L-2105D
- Volvo 97310
- ZF TE-ML 16C/17B/19B/21A



DESCRIPTION

emka®

Quality engineered in Germany



Hypoid SAE 85W90

High-Performance gear oil

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	891	Kg/m ³	ASTM D 1298
Viscosity at 40°C	137,0	mm ² /s	ASTM D 445
Viscosity at 100°C	16,3	mm ² /s	ASTM D 445
Viscosity index	160		ASTM D 2270
Flashpoint	212	°C	ASTM D 92
Pourpoint	-33	°C	ASTM D 97

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	1355000	20 Liter	1355030
205 Liter	1355010	4 x 5 Liter	1355050
60 Liter	1355020	12 x 1 Liter	1355070

EMKA Schmiertechnik GmbH
Schmalbachstrasse 19
74626 Bretzfeld, Germany

Telefon +49 7946 94 470-0
Telefax +49 7946 94 470-70
E-Mail info@emka-oil.de

www.emka-oil.de

