



PERMAGLIDE®

PERFECT **RUNNING**

PERMAGLIDE® P2 PLAIN BEARINGS

LOW-MAINTENANCE, FOR APPLICATIONS
WITH GREASE OR LIQUID LUBRICATION

TAKING RESPONSIBILITY IN A CHANGING WORLD



RHEINMETALL

IMPORTANT INSTRUCTIONS

All information in this catalogue is non-binding. We can accept no responsibility for its correctness and completeness. We always welcome feedback about any errors in the catalogue, and will correct them in future editions.

We reserve the right to change the product specifications, materials, the appearance and the scope of supply of our products at any time. The figures in the catalogue are therefore non-binding.

Before the installation, always check whether the purchased product is suitable for the intended purpose. Please note that the products offered in the catalogue are not intended for use in aircraft and spacecraft.

The installation must also always be carried out by qualified personnel. Illustrations, schematic diagrams and other data are provided for the purpose of explanation and depiction, and cannot be taken as the basis for installation.

Reprinting, imitation and reproduction of this catalogue in whole or in part is permitted only with our written consent and with reference to the source.

On publication of this catalogue, all previous versions become invalid.

MOTORSERVICE GROUP

QUALITY AND SERVICE FROM A SINGLE SOURCE

The Motorservice Group is the sales organisation for the global aftermarket activities of Rheinmetall. It is a leading supplier of engine components for the independent aftermarket. With the premium brands Kolbenschmidt, Pierburg, TRW Engine Components and the BF brand, Motorservice offers its customers a wide and comprehensive range of top-quality products from a single source. Motorservice is also a sales partner for maintenance-free and low-maintenance PERMAGLIDE® plain bearings and other components for industry and technical trade.

KS GLEITLAGER

Within Rheinmetall, KS Gleitlager GmbH is the specialist for high-precision sliding elements. The introduction of new technologies in production and surface finishing, innovative developments and a clear customer focus have made KS Gleitlager into one of the world's leading suppliers of engine bearings and dry plain bearings (PERMAGLIDE®).

RHEINMETALL

TECHNOLOGIES FOR THE MOBILITY OF THE FUTURE

As a global automotive supplier, Rheinmetall's expertise in air supply systems, emission control and pumps and in the development, manufacture and spare parts supply of pistons, engine blocks and plain bearings puts it right at the top of the relevant markets. Product development is carried out in close cooperation with well-known automotive manufacturers.

Permaglide® is a registered trademark of KS Gleitlager GmbH

Edited by:
Motorservice, Application technology and marketing

Layout and production:
Motorservice, Marketing
Die Neckarprinzen GmbH, Heilbronn

This document must not be reprinted, duplicated or translated in full or in part without our prior written consent or without reference to the source of the material.

All content including pictures and diagrams is subject to alteration. No liability accepted.

Published by:
© MS Motorservice Deutschland GmbH

1 DESCRIPTION OF MATERIAL

PERMAGLIDE® P2 is a low-maintenance sliding material for lubricated applications. This composite, multi-layered system excels through its high rigidity, durability and resistance to oscillation and vibration. These properties are largely achieved by a sliding layer system made of polyvinylidenefluoride (PVDF) and polytetrafluoroethylene (PTFE), plus mineral fillers.

PERMAGLIDE® P2 materials offer the following advantages over comparable products:

- High wear resistance
- Good damping characteristics
- Good chemical resistance
- Minimal swelling tendency
- Insensitivity to shocks and impacts
- Insensitivity to high edge loading

2 MATERIAL COMPOSITION AND MATERIAL VERSIONS




Fig. 1: Microsection of P203

P200

- Ready to install, with lubricating pockets
- Lubricating pockets act as a grease reservoir in mixed friction systems

P202

- With machining allowance, without lubricating pockets
- With machining allowance for higher precision with additional machining when installed

P203

- Ready to install, without lubricating pockets
- Smooth surfaces for fluid friction

3 CHARACTERISTIC PROFILES

The general performance characteristics of composite materials depend on the properties of the polymers used. The balanced characteristic profile of the PERMAGLIDE® P2 is achieved thanks to the ideal composition of the sliding layer. The primary component and therefore most important influencing factor is a polymer matrix of polyvinylidenfluoride (PVDF). In contrast, the majority of comparable products from other manufacturers are produced from low-cost polyoxymethylene (POM). The radial diagrams (Fig. 2) show a relative comparison of characteristic features. Points that lie far outside in the direction of the arrow indicate a very marked characteristic.

PVDF attains a high level for most characteristics, and is therefore a universal material for plain bearing applications. By adding fillers, in the PERMAGLIDE® P2 resistance to wear and abrasion and emergency running characteristics have been further improved. The POM polymer, on the other hand, is generally deficient in terms of damping, toughness and resistance to chemicals.





Fig. 2: Radial diagrams

4 TECHNICAL DATA

The performance limits of plain bearings are described in so-called pv value diagrams (Fig. 3). The product of surface pressure (p) and circumferential speed (v) is equivalent to the input power per bearing surface. If an operating point lies inside the curve, it can be assumed that PERMAGLIDE® P2 plain bearings can be used.




Fig. 3: pv value [MPa·m/s], limit curve (values apply at room temperature)

Characteristic values, load limit	Designation	Unit	Value
Types of pressure			
Static	p_{stat}	MPa	250
Dynamic	p_{dyn}	MPa	140
Speed			
Rotating	v_{rot}	[m/s]	3.3
Linear	v_{lin}	[m/s]	6
Continuous operating temperature			
Min.	T_{min}	°C	-40
Max.	T_{max}	°C	110
Short-time	T_{short}	°C	140
Coeff. of therm. expansion	α_{steel}	$10^{-5} 1/K$	1.1
Thermal conductivity	λ_{steel}	W/m/K	<40

5 APPLICATIONS

PERMAGLIDE® covers a broad range of applications, e.g. as main bearings in gear pumps in the chemical industry (Fig. 4). The bearings come into direct contact with aggressive pumping media, where abrasion resistance and chemical compatibility are what matter. Fluoropolymers are extremely non-absorbent, which means that virtually none of the surrounding fluid is absorbed and the sliding surface is not prone to swelling.

PERMAGLIDE® P200 is also used in the bearing assembly of maintenance-free ball heads, in the steering linkage of tractors, for example (Fig. 5). In extremely tough operating conditions, the bearings are permanently exposed to the influence of dirt, temperature fluctuations and vibrations with severe shocks. Despite this exposure, precise guidance is guaranteed over a long service life.

PERMAGLIDE® P2 is used for thrust bearings in shock absorber systems (Fig. 6). A high guiding accuracy under changing operating conditions is demanded from this bearing. P2 has proven itself especially suitable for this particular application. On poor surfaces, P2 has a considerably longer service life, which the competition cannot match.

PERMAGLIDE® is used in radial piston engines (Fig. 7). These engines generate very high torques at low revolutions. It's a straightforward principle: Hydraulic mechanisms move pistons radially. Rollers transfer the radial force to a cam track, thereby transforming it into a rotary movement. The rollers are mounted on half-shells of P203. They are subject to extremely high pressure while only mixed friction is present.





Fig. 4: Gear pump application

Fig. 5: Application in steering linkage ball heads



Fig. 6: Application in shock absorber systems



01 Piston
02 Roller
03 PERMAGLIDE® half-shell

Fig. 7: Application in radial piston system

6 APPLICATION PARAMETERS

Low-maintenance P2 plain bearings can be used in systems with lifetime lubrication.

Suitable lubricants are all commonly available types of grease based on

- Lithium (resistance to ageing)
- Barium (good adhesion)
- Aluminium (good wettability) and oil
- HLP hydraulic oil
- Bed track oil
- Mineral oil



Important:

The suitability of bio-oils must first be verified in tests, due to the ketone and ester they contain.

The operational reliability and service life of PERMAGLIDE® P2 plain bearings are largely dependent on the interacting sliding partner. Good conditions are produced by the use of both stainless or hard chrome-plated steel and hard-anodised aluminium. The interacting

sliding partner should have a surface roughness in the region of Rz 0.8 to 1.5 µm. Standard plain bearing bushes are dimensioned as low-cost catalogue goods to DIN ISO 3547. Adapted designs and individual plain bearing solutions can also be produced.



Motorservice offers you assistance with designing your plain bearings.


7 VERSIONS OF THE PERMAGLIDE® P2



PAP bushes
P200, P202*, P203*




PAW thrust washers
P200, P202*, P203*



PAS strips
P200, P202*, P203*

PERMAGLIDE® – THE ADVANTAGES AT A GLANCE

- Central management and production – Made in Germany
- Advice, calculation and plain bearing design
- Standard parts to DIN ISO 3547
- Special designs as per customers' wishes
- Top quality standards of the German automotive industry
- Stable, reliable processes:
 - Strength tests parallel to production
 - Continuous dimensional checks
- Material development
- Test benches to suit real-life conditions, based on customers' requirements
- Stocking of parts, availability and logistical performance



HEADQUARTERS:

MS Motorservice Deutschland GmbH

Rudolf-Diesel-Straße 9

71732 Tamm, Deutschland

Telefon: +49 7141 8661-434

Telefax: +49 7141 8661-430

www.permaglide.com

www.permaglide.com

© MS Motorservice Deutschland GmbH – 50003846-02 – EN – 05/15 (062024)

