

# Deutsch DT

## Crimp Connector

c-062

 <p><b>Crimp Connector Deutsch DT</b> TE Connectivity Round Plug Cross Section 0,5 - 1,3 mm Diameter 1,59 mm PU 50 Pieces</p> <p><b>50253559</b></p>	 <p><b>Crimp Connector Deutsch DT</b> TE Connectivity Round Plug Cross Section 0,85 - 2 mm Diameter 1,59 mm PU 50 Pieces</p> <p><b>50253560</b></p>	 <p><b>Crimp Connector Deutsch DT</b> TE Connectivity Round Connector Sleeve Cross Section 0,5 - 1 mm Diameter 1,59 mm PU 50 Pieces</p> <p><b>50253561</b></p>	 <p><b>Crimp Connector Deutsch DT</b> TE Connectivity Round Connector Sleeve Cross Section 0,75 - 2 mm Diameter 1,59 mm PU 50 Pieces</p> <p><b>50253562</b></p>
---	--	--	--

### » DEUTSCH DT AND DTM SERIES



The products in the Deutsch DT series are very robust and also work faultlessly at extreme ambient temperatures of -55 °C to 125 °C. The thermoplastic connector housing and the high quality silicone seals are protected against environmental influences like humidity, dirt and lubricants. The plug connectors have an impermeable safety lock. Up to 13 ampere current load are possible per contact. In summary, the Deutsch DT series is one of the most resilient connector systems and thus optimally suited to applications under the bonnet, on the gear unit, on the chassis and in the vehicle's interior.

As a further development of the DT series, we offer the DTM series, which was specially designed for low-current applications. In contrast to the DT series, the sealing ring is positioned inside the pin housing and therefore cannot be damaged by external influences. Contacts with a pin diameter of 1 mm are used, which are designed for a max. current of 7.5 amperes (with a cable cross-section of 0.5 mm<sup>2</sup>). The plug-in housings are available with 2, 3, 4, 6, 8 and 12 poles.

