

according to Regulation (EC) No 1907/2006

MEYLE SAE 75W-90 HC LS

Revision date: 04.04.2018 Product code: 014_019_2600-3-4 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

MEYLE SAE 75W-90 HC LS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Gear oil

1.3. Details of the supplier of the safety data sheet

Company name: Meyle AG
Street: Merkurring 111
Place: D-22143 Hamburg

Telephone: +49 40 67 506 510 Telefax: +49 40 67 506 506

e-mail: contact@meyle.com
Internet: www.meyle.com

1.4. Emergency telephone Giftnotruf Göttingen

number: +49 551 19 24 0 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Causes serious eye irritation.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Pentene, 2,4,4-trimethyl-, sulfurized

Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)

Long-chain alkyl amine

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves and eye/face protection.



according to Regulation (EC) No 1907/2006

MEYLE SAE 75W-90 HC LS

Revision date: 04.04.2018 Product code: 014_019_2600-3-4 Page 2 of 9

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container to of the disposal according to local regulations.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification according to Regula	tion (EC) No. 1272/2008 [CLP]			
72623-87-1	Baseoil - unspecified, Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based				
	276-738-4	649-483-00-5	01-2119474889-13		
	Asp. Tox. 1; H304				
	Pentene, 2,4,4-trimethyl-, sulfurized				
	273-103-3				
	Skin Sens. 1, Aquatic Chronic 4; H317 H413				
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)				
	931-384-6		01-2119493620-38		
	Flam. Liq. 3, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 2; H226 H302 H318 H317 H411				
	Long-chain alkyl amine			< 1 %	
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H302 H314 H317 H400 H410				
	O,O,O-triphenyl phosphorothioate				
	209-909-9				
	Repr. 2, Aquatic Chronic 4; H361	H413			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

Change contaminated clothing.

Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

In case of inhalation of aerosols/spray mist/splash spots: Consult physician. Provide fresh air.

Avoid breathing dust/fume/gas/mist/vapours/spray. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

After contact with skin

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.

If skin irritation or rash occurs: Get medical advice/attention.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

In case of troubles or persistent symptoms, consult an ophthalmologist.





according to Regulation (EC) No 1907/2006

MEYLE SAE 75W-90 HC LS

Revision date: 04.04.2018 Product code: 014_019_2600-3-4 Page 3 of 9

After ingestion

Rinse mouth immediately and drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

Caution if victim vomits: Risk of aspiration! Aspiration hazard: Call a physician immediately.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Carbon dioxide (CO2). Dry extinguishing powder. Foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance itself, combustion products, resulting gases:

Carbon dioxide (CO2). Carbon monoxide Sulphur oxides. Phosphorus oxides. Hydrogen sulphide (H2S).

5.3. Advice for firefighters

carbon black In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Dispose of waste according to applicable legislation.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Special danger of slipping by leaking/spilling product.

Wear suitable protective clothing.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Protect skin by using skin protective cream. Wash hands before breaks and after work.

Conditions to avoid: aerosol or mist generation.

Advice on protection against fire and explosion

No special measures are necessary.





according to Regulation (EC) No 1907/2006

MEYLE SAE 75W-90 HC LS

Revision date: 04.04.2018 Product code: 014_019_2600-3-4 Page 4 of 9

When using do not smoke.

Fire class: B (DIN-/EN-Norms: EN2)

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Keep away from heat. Keep/Store only in original container.

Advice on storage compatibility

Do not store together with:Food and fodder, Oxidizing agents.

Further information on storage conditions

If product enters soil, it will be mobile and may contaminate groundwater. Keep away from heat.

7.3. Specific end use(s)

Gear oil

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective and hygiene measures

When using do not eat, drink or smoke.

Change contaminated clothing.

Wash hands before breaks and after work.

Protect skin by using skin protective cream.

Keep away from food, drink and animal feedingstuffs.

Do not breathe vapour.

Eye/face protection

In fine dispersion/spraying/misting: Wear protective gloves/protective clothing.

Hand protection

Wear suitable gloves.

Skin protection

In fine dispersion/spraying/misting: Wear protective gloves/protective clothing.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: yellow-brown Odour: characteristic

Test method

pH-Value: not applicable DIN 51369

Changes in the physical state

Pour point: ISO 3016

Pourpoint:: <-33 °C DIN ISO 3016

Flash point: >200 °C ISO 2592

Ignition temperature: No data available

Vapour pressure: <0,1 hPa calculated.

(at 20 °C)

Density (at 15 °C): ~0,86 g/cm³ DIN 51757



according to Regulation (EC) No 1907/2006

MEYLE SAE 75W-90 HC LS

Revision date: 04.04.2018 Product code: 014_019_2600-3-4 Page 5 of 9

Water solubility: practically insoluble

(at 20 °C)

Solubility in other solvents

Soluble in hydrocarbons (mineral oil.)

Viscosity / kinematic: 13,5-18,5 mm²/s DIN 51562

(at 100 °C)

Solvent separation test:

No data available

Solvent content:

none Solvents

9.2. Other information

none

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

No thermal decomposition if properly stored / handled /transported.

Onset of decomposition at elevated temperatures (>65°C)

10.3. Possibility of hazardous reactions

possible with strong oxidizing agents.

This product is stable under normal conditions. Hazardous reactions are unlikely.

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Oxidizing agents, strong.

10.6. Hazardous decomposition products

none

Further information

No thermal decomposition if properly stored / handled /transported.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

No data available.

Irritant effect on the respiratory tract: Do not breathe gas/vapour.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
	Reaction products of bis(amines, C12-14 alkyl (bra		tan-2-yl)dithi	ophosphoric acid with pho	sphorus oxide, propylene	oxide and
	oral	ATE mg/kg	500			
	Long-chain alkyl amine					
	oral	LD50 mg/kg	> 500	Rat		
	dermal	LD50 1000 mg/kg	201 - I	Rabbit		
	inhalative vapour	ATE	0,5 mg/l			
	inhalative aerosol	ATE	0,05 mg/l			



according to Regulation (EC) No 1907/2006

MEYLE SAE 75W-90 HC LS

Revision date: 04.04.2018 Product code: 014_019_2600-3-4 Page 6 of 9

Irritation and corrosivity

Irritant effect on the skin: none

Frequent and prolonged eye contact may cause eye irritation.

Sensitising effects

Due to the very low concentration of sensitizing substances, the finished product can be assumed not to be skin-sensitizing.

Carcinogenic/mutagenic/toxic effects for reproduction

The product is not classified.

STOT-repeated exposure

Frequently or prolonged contact with skin may cause dermal irritation.

Specific effects in experiment on an animal

No data available.

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

Practical experience

Observations relevant to classification

Has de-greasing effect on the skin.

Other observations

No special hazards known when the product is properly used and the precautionary measures indicated are observed.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d] Species	Source	Method
72623-87-1	Baseoil - unspecified, Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based				
	Acute fish toxicity	LC50 > 100 mg/l	96 h	OECD 203	
	Acute algae toxicity	ErC50 >= 100 mg/l	72 h	OECD 201	
	Acute crustacea toxicity	EC50 > 10 000 mg/l	48 h	OECD 202	

12.2. Persistence and degradability

Due to its low solubility in water the product is almost completely mechanically separated in biological sewage plants. Poorly eliminated from water.

Not easily bio-degradable (according to OECD-criteria). Product is partially biodegradable. Significant residues remain.

Post-use oils must not be discharged into the sewer system or into surface waters nor must they be allowed to enter the soil.

12.3. Bioaccumulative potential

No data available.

Do not allow uncontrolled discharge of product into the environment.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
72623-87-1	Baseoil - unspecified, Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	> 6





according to Regulation (EC) No 1907/2006

MEYLE SAE 75W-90 HC LS

Revision date: 04.04.2018 Product code: 014_019_2600-3-4 Page 7 of 9

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

Aquatic organisms: No data available. Effects in sewage plants No data available.

No data available.

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

The waste codes stated are recommendations based on the expected use of the substance and may be re-assigned to other waste codes by the user, if applicable.

Dispose of waste according to applicable legislation.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Waste disposal number of waste from residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated

engine, gear and lubricating oils; hazardous waste

Waste disposal number of used product

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated

engine, gear and lubricating oils; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Dispose of this material and its container to hazardous or special waste collection point. Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: Gear oil

14.3. Transport hazard class(es):14.4. Packing group:No dangerous good in sense of this transport regulation.No dangerous good in sense of this transport regulation.

Other applicable information (land transport)

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: Gear oi

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.



according to Regulation (EC) No 1907/2006

MEYLE SAE 75W-90 HC LS

Revision date: 04.04.2018 Product code: 014 019 2600-3-4 Page 8 of 9

14.4. Packing group: No dangerous good in sense of this transport regulation.

Other applicable information (inland waterways transport)

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number: No dangerous good in sense of this transport regulation.

Gear oil 14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation. 14.3. Transport hazard class(es): 14.4. Packing group: No dangerous good in sense of this transport regulation.

Other applicable information (marine transport)

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: Gear oil

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. 14.4. Packing group:

Other applicable information (air transport)

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information

H304

According to EC directives or the corresponding national regulations the product does not have to be labelled.

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

May be fatal if swallowed and enters airways.

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Rel

Sens. 1; H317	Calculation method
tic Chronic 3; H412	Calculation method
elevant H and EUH statement	s (number and full text)
H226 Flamr	nable liquid and vapour.
H302 Harm	ful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.



according to Regulation (EC) No 1907/2006

Revision date: 04.04.2018	Product code: 014_019_2600-3-4	Page 9 of 9
H319	Causes serious eye irritation.	
H330	Fatal if inhaled.	
H361	Suspected of damaging fertility or the unborn child.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
H413	May cause long lasting harmful effects to aquatic life.	

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

reflect the state of our current knowledge and experience and shall not be construed as warranted

characteristics. Any warranty for accuracy and completeness shall be expressly excluded.