#### 42117 Wuppertal

Date printed 05.03.2024, Revision 05.03.2024



Version 7.0. Supersedes version: 6.0 Page 1 / 16

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Engine Oil 5W-30 Article number: 50 10 1150, 50 10 1151, 50 10 1152, 50 10 1153, 50 10 1154 UFI: Q641-V918-Q00H-C01N

- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- 1.2.1 Relevant uses

Company

Engine oil

#### 1.2.2 Uses advised against

None known.

#### 1.3 Details of the supplier of the safety data sheet

SWAG Autoteile GmbH Am Kiesberg 4-6 42117 Wuppertal / GERMANY Phone +49 (0)202 26454-0 Fax +49 (0)202 26454-5000 Homepage www.swag.de E-mail info@swag.de Address enquiries to

Technical information	info@swag.de
Safety Data Sheet	info@swag.de

#### 1.4 **Emergency telephone number**

Advisory body

+49 (0)89-19240 (24h) (English)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Skin Sens. 1: H317 May cause an allergic skin reaction.

#### Label elements 2.2

Hazard pictograms

The product is required to be labelled in accordance with regulation CLP.

Signal word	WARNING
Contains:	C14-16-18 Alkyl phenol
Hazard statements	H317 May cause an allergic skin reaction.
Precautionary statements	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice / attention. P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

### 42117 Wuppertal

Date printed 05.03.2024, Revision 05.03.2024



Version 7.0. Supersedes version: 6.0 Page 2 / 16

#### 2.3 Other hazards

Physico-chemical hazards	No particular hazards known.
Human health dangers	Frequent persistent contact with the skin can cause skin irritation.
Environmental hazards	Does not contain any PBT or vPvB substances. Contains no ingredients with endocrine-disrupting properties.
Other hazards	Further hazards were not determined with the current level of knowledge.

#### **SECTION 3: Composition / Information on ingredients**

#### 3.1 Substances

not applicable

#### 3.2 Mixtures

#### The product is a mixture.

Range [%]	Substance
30 - < 60	Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)
	CAS: 93819-94-4, EINECS/ELINCS: 298-577-9, Reg-No.: 01-2119543726-33-XXXX
	GHS/CLP: Skin Irrit. 2: H315 - Eye Dam. 1: H318 - Aquatic Chronic 2: H411
	SCL [%]: >6,25 - 100: Skin Irrit. 2: H315, >10 - 12,5: Eye Irrit. 2: H319, > 12,5: Eye Dam. 1: H318
1 - < 2,5	C14-16-18 Alkyl phenol
	CAS: 1190625-94-5, EINECS/ELINCS: 931-468-2, Reg-No.: 01-2119498288-19-XXXX
	GHS/CLP: Skin Sens. 1B: H317 - STOT RE 2: H373
1 - < 2,5	Bis(nonylphenyl)amine
	CAS: 36878-20-3, EINECS/ELINCS: 253-249-4, Reg-No.: 01-2119488911-28-XXXX
	GHS/CLP: Aquatic Chronic 4: H413
1 - < 2,5	Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt)
	CAS: 64742-65-0, EINECS/ELINCS: 265-169-7, Reg-No.: 01-2119471299-27-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-56-9, EINECS/ELINCS: 265-159-2, EU-INDEX: 649-469-00-9, Reg-No.: 01-2119480132-48-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Paraffin oils (petroleum), catalytic dewaxed heavy
	CAS: 64742-70-7, EINECS/ELINCS: 265-174-4, EU-INDEX: 649-477-00-2, Reg-No.: 01-2119487080-42-XXXX
	GHS/CLP: Asp. Tox. 1: H304

#### Comment on component parts

For full text of H-statements and R-phrases: see SECTION 16.

#### **SECTION 4: First aid measures**

4.1	Description of first aid measures	
	General information	Change soaked clothing.
	Inhalation	Ensure supply of fresh air. In the event of symptoms seek medical treatment.
	Skin contact	In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.
	Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
	Ingestion	Consult a doctor immediately. Rinse out mouth and give plenty of water to drink. Do not induce vomiting.

Date printed 05.03.2024, Revision 05.03.2024

## SWAG Autoteile GmbH

42117 Wuppertal



Version 7.0. Supersedes version: 6.0 Page 3 / 16

	,	un in a second	
4.2	Most important symptoms and a	offects, both acute and delayed	
4.2	2 Most important symptoms and effects, both acute and delayed If swallowed or in the event of vomiting, risk of product entering the lungs.		
4.2			
4.3	Indication of any immediate med	dical attention and special treatment needed	
		Treat symptomatically. Forward this sheet to your doctor.	
SEC	TION 5: Fire-fighting measures		
5.1	Extinguishing media		
	Suitable extinguishing media	Fire extinguishing method of surrounding areas must be considered. Foam, dry powder, water spray jet, carbon dioxide	
	Extinguishing media that must not be used	Full water jet.	
5.2	Special hazards arising from the	e substance or mixture	
		Risk of formation of toxic pyrolysis products.	
		Carbon monoxide (CO)	
		Sulphur oxides (SOx). Nitrogen oxides (NOx).	
		Hydrogen sulfide ((H2S).	
5.3	Advice for firefighters		
	5	Do not inhale explosion and/or combustion gases.	
		Use self-contained breathing apparatus.	
		Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.	
SEC	TION 6: Accidental release measu	ures	
6.1	Personal precautions protective	e equipment and emergency procedures	
•		High risk of slipping due to leakage/spillage of product.	
		Forms slippery surfaces with water.	
		Ensure adequate ventilation.	
		Use personal protective equipment (protective gloves, safety glasses, protective clothing).	
6.2	Environmental precautions		
		Prevent spread over a wide area (e.g. by containment or oil barriers). Do not discharge into the drains/surface waters/groundwater.	
6.3	Methods and material for contain	nment and cleaning up	
		Take up with absorbent material (e.g. general-purpose binder).	
		Dispose of absorbed material in accordance within the regulations.	
6.4	Reference to other sections		
		See SECTION 8+13	
SEC	TION 7: Handling and storage		
7.1	Precautions for safe handling		
		Avoid formation of aerosols.	
		Do not smoke. Fire class (DIN EN 2): B	
		Wash hands before breaks and after work.	
		Do not eat, drink or smoke when using this product.	
		Use barrier skin cream.	

Take off contaminated clothing and wash before reuse.

Cloths contaminated with product should not be kept in trouser pockets.

# SWAG Autoteile GmbH 42117 Wuppertal

Date printed 05.03.2024, Revision 05.03.2024



Version 7.0. Supersedes version: 6.0 Page 4 / 16

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container. Prevent penetration into the ground.

Do not store together with oxidizing agents. Do not store together with food and animal food/diet.

Keep container tightly closed. Protect from heat/overheating.

7.3 Specific end use(s)

See product use, SECTION 1.2

### SWAG Autoteile GmbH

#### 42117 Wuppertal

Date printed 05.03.2024, Revision 05.03.2024

Version 7.0. Supersedes version: 6.0 Page 5 / 16

**SECTION 8: Exposure controls / personal protection** 

#### 8.1 Control parameters

#### Ingredients with occupational exposure limits to be monitored (UK)

Substance	
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-e	extract)
CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-	-No.: 01-2119484627-25-XXXX
Long-term exposure: 5 mg/m <sup>3</sup> , oil mist	
Short-term exposure (15-minute): 10 mg/m <sup>3</sup>	
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-	-extract)
CAS: 64742-56-9, EINECS/ELINCS: 265-159-2, EU-INDEX: 649-469-00-9, Reg-	-No.: 01-2119480132-48-XXXX
Long-term exposure: 1200 mg/m <sup>3</sup>	

#### Ingredients with occupational exposure limits to be monitored EU (2004/37/EG)

not relevant

DNEL

nonylphenyl)amine, CAS: 36878-20-3	
strial, dermal, Long-term - systemic effects, 5 mg/kg bw/day	
eral population, dermal, Long-term - systemic effects, 2,5 mg/kg bw/day	
eral population, oral, Long-term - systemic effects, 0,25 mg/kg bw/day	4 7
tillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-5	94-7
strial, inhalative, Long-term - systemic effects, 2.73 mg/m <sup>3</sup>	
strial, inhalative, Long-term - local effects, 5.58 mg/m <sup>3</sup>	
strial, dermal, Long-term - systemic effects, 970 μg/kg bw/day	
eral population, inhalative, Long-term - local effects, 1.19 mg/m <sup>3</sup>	
eral population, oral, Long-term - systemic effects, 740 μg/kg bw/day	
llates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742	-56-9
strial, inhalative, Long-term - systemic effects, 2,73 mg/m <sup>3</sup>	
strial, inhalative, Long-term - local effects, 5,58 mg/m³	
strial, dermal, Long-term - systemic effects, 0,97 mg/kg bw/day	
eral population, oral, Long-term - systemic effects, 0,74 mg/kg bw/day	
llates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0	
strial, inhalative, Long-term - systemic effects, 2,73 mg/m <sup>3</sup>	
strial, inhalative, Long-term - local effects, 5,58 mg/m <sup>3</sup>	
strial, dermal, Long-term - systemic effects, 970 μg/kg bw/day	
eral population, oral, Long-term - local effects, 740 μg/kg bw/day	
bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4	
strial, inhalative, Long-term - systemic effects, 8,31 mg/m <sup>3</sup>	
strial, dermal, Long-term - systemic effects, 0,58 mg/kg bw/day	
eral population, inhalative, Long-term - systemic effects, 2,11 mg/m <sup>3</sup>	
eral population, dermal, Long-term - systemic effects, 0,29 mg/kg bw/day	
eral population, oral, Long-term - systemic effects, 0,24 mg/kg bw/day	
iffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7	
strial, inhalative, Long-term - systemic effects, 2.73 mg/m <sup>3</sup>	
strial, inhalative, Long-term - local effects, 5.58 mg/m <sup>3</sup>	
strial, dermal, Long-term - systemic effects, 970 µg/kg bw/day	

# SWAG Autoteile GmbH 42117 Wuppertal

PNEC



Page 6 / 16

Version 7.0. Supersedes version: 6.0

Date printed 05.03.2024, Revision 05.03.2024

gener	ral population, oral, Long-term - systemic effects, 740 µg/kg bw/day
-	16-18 Alkyl phenol, CAS: 1190625-94-5
Indus	trial, inhalative, Long-term - systemic effects, 1,17 mg/m <sup>3</sup>
Indus	trial, dermal, Long-term - systemic effects, 300 μg/kg bw/d
Subs	tance
Bis(n	onylphenyl)amine, CAS: 36878-20-3
fresh	water, 412 µg/L
seaw	ater, 41.2 µg/L
sedim	nent (freshwater), 1 mg/kg sediment dw
sedim	nent (seawater), 0.1 mg/kg sediment dw
Desti	llates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
oral (f	food), 9,33 mg/kg
Distill	ates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-
oral (	food), 9,33 mg/kg food
Distill	lates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
oral (f	food), 9,33 mg/kg food
Zinc b	bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
fresh	water, 0,004 mg/l
seaw	ater, 0,004 mg/l
sewa	ge treatment plants (STP), 100 mg/l
sedim	nent (freshwater), 0,012 mg/kg dw
sedim	nent (seawater), 0,001 mg/kg dw
soil, (	0,005 mg/kg
oral (	food), 10,67 mg/kg
Paraf	fin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
oral (	food), 9.33 mg/kg food
C14-1	16-18 Alkyl phenol, CAS: 1190625-94-5
fresh	water, 100 µg/l
seaw	ater, 10 μg/l
sewa	ge treatment plants (STP), 100 mg/l
sedim	nent (freshwater), 4266,16 mg/kg dw
sedim	nent (seawater), 426,62 mg/kg dw
م اند	352,58 mg/kg dw

### 42117 Wuppertal

Date printed 05.03.2024, Revision 05.03.2024



Version 7.0. Supersedes version: 6.0 Page 7 / 16

#### 8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,11 mm: Nitrile rubber, >480 min (EN 374-1/-2/-3).
Skin protection	Light protective clothing.
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin.
Respiratory protection	In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection. Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	liquid
Color	light brown
Odor	characteristic
Odour threshold	No information available.
pH-value	not applicable
pH-value [1%]	No information available.
Boiling point or initial boiling point and boiling range [°C]	No information available.
Flash point [°C]	>195 (ISO 2592)
Flammability	not applicable
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	<0,01 (20°C)
Density [g/cm³]	ca. 0,849 (DIN 51757) (15 °C / 59,0 °F)
Relative density	not determined
Bulk density [kg/m³]	not applicable
Solubility in water	virtually insoluble
Solubility other solvents	No information available.
Partition coefficient n-octanol/water (log value)	No information available.
Kinematic viscosity	ca. 10,1 mm²/s (100°C) (DIN 51562/T1) >20,5 mm²/s (40°C)
Relative vapour density	No information available.
Melting point [°C]	<-36 (DIN ISO 3016)
Auto-ignition temperature [°C]	No information available.
Decomposition temperature [°C]	>65°C
Particle characteristics	No information available.

### 42117 Wuppertal

Date printed 05.03.2024, Revision 05.03.2024



Version 7.0. Supersedes version: 6.0 Page 8 / 16

#### 9.2 Other information

Pour point: ca -36°C

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

See SECTION 10.3.

#### 10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

#### 10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

#### 10.4 Conditions to avoid

Strong acids. Strong heating, because the thermal decomposition starts from > 65°C.

#### 10.5 Incompatible materials

Oxidizing agent Acids Strong basic compounds

#### 10.6 Hazardous decomposition products

In the case of heating following (decomposition) products may occure: Hydrogen sulfide (H2S).

### SWAG Autoteile GmbH

#### 42117 Wuppertal

Date printed 05.03.2024, Revision 05.03.2024



Version 7.0. Supersedes version: 6.0 Page 9 / 16

#### **SECTION 11: Toxicological information**

Product

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity

Based on available data, the classification criteria are not met.

ATE-mix, oral, >2000 mg/kg bw
Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
_D50, oral, Rat, 5000 mg/kg bw
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
_D50, oral, Rat, 5000 mg/kg bw
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
_D50, oral, Rat, >5000 mg/kg bw (OECD 401)
NOAEL, oral, Rat, >1000 mg/kg bw (OECD 421)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
_D50, oral, Rat, 5000 mg/kg bw
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
_D50, oral, Rat, 2600 mg/kg
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
_D50, oral, Rat, >5000 mg/kg bw
_OAEL, oral, Rat, 125 mg/kg bw/day
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
_D50, oral, Rat (female), >2000 mg/kg bw

#### Acute dermal toxicity

Based on available data, the classification criteria are not met.

#### Product

ATE-mix, dermal, >2000 mg/kg bw

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LD50, dermal, Rabbit, 2000 - 5 00 mg/kg bw

Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9

LD50, dermal, Rabbit, >5000 mg/kg bw (OECD 403)

NOAEL, dermal, Rat, >2000 mg/kg bw (OECD 414)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

LD50, dermal, Rabbit, > 2000 - 5000 mg/kg bw

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4

LD50, dermal, Rabbit, >3160 mg/kg bw/day

Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7

LD10, dermal, Rabbit, >2000 mg/kg bw

NOAEL, dermal, Rabbit, >1000 mg/kg bw/day

C14-16-18 Alkyl phenol, CAS: 1190625-94-5

LD50, dermal, Rat, >2000 mg/kg bw

#### Acute inhalational toxicity

Based on available data, the classification criteria are not met.

Product

ATE-mix, inhalation (vapour ), >20 mg/L

### SWAG Autoteile GmbH

42117 Wuppertal

Date printed 05.03.2024, Revision 05.03.2024



Version 7.0. Supersedes version: 6.0 Page 10 / 16

ubstance
estillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
C50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h
stillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
C50, inhalative, Rat, >5,53 mg/l air (OECD 403)
stillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
C50, inhalative, Rat, 2,18 - 5,53 mg/L air 4h, 4h
nc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
C50, inhalative, Rat, >2 mg/l
araffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
C50, inhalative, Rat, 18 - 5.53 mg/L air, 4h
DAEC, inhalative, Rat, 980 mg/m³ air

#### Serious eye damage/irritation

No classification due to substance-specific concentration limits. CAS 93819-94-4: >10% - <12,5% Eye Irrit. 2

Substance	
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9	
Eye, non-irritating	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0	
Eye, non-irritating	

#### Skin corrosion/irritation

Based on the available information, the classification criteria are not fulfilled.

Substance		
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9		
dermal, non-irritating		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0		
dermal, non-irritating		

**Respiratory or skin sensitisation** May cause an allergic skin reaction.

Substance		
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9		
dermal, non-sensitizing		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0		
dermal, non-sensitizing		

Based on the available information, the classification criteria are not fulfilled.

**Specific target organ toxicity** — Based on the available information, the classification criteria are not fulfilled. single exposure

Specific target organ toxicity — repeated exposure

Sub	ostance
Bis(	(nonylphenyl)amine, CAS: 36878-20-3
NO	EL, oral, Rat, 100 mg/kg bw/day
Des	stillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
NOA	AEL, dermal, Rat, 30 - 2000 mg/kg bw/day
NOA	AEL, dermal, Rabbit, 1000 mg/kg bw/day
NOA	AEC, inhalative, Rat, 980 mg/m³ air
LOA	AEL, oral, Rat, 125 mg/kg bw/day
Dist	tillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9

# SWAG Autoteile GmbH 42117 Wuppertal

Date printed 05.03.2024, Revision 05.03.2024



Version 7.0. Supersedes version: 6.0 Page 11 / 16

NOAEC, inhalative, Rat, 980 mg/m <sup>3</sup> , no adverse effect observed	
LOAEL, oral, Rat, 125 mg/kg bw/day, adverse effect observed	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0	
NOAEL, inhalative, Rat, 980 mg/m <sup>3</sup> air, no adverse effect observed	
LOAEL, dermal, mouse, 100 mg/kg bw/day, The effects observed are not sufficient for classification.	
LOAEL, oral, Rat, 125 mg/kg bw/day, The effects observed are not sufficient for classification.	
C14-16-18 Alkyl phenol, CAS: 1190625-94-5	
NOAEL, oral, Rat, 30 - 100 mg/kg bw/day	

#### Mutagenicity

Based on the available information, the classification criteria are not fulfilled.

Substance	
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9	
in vitro, negativ	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0	
in vitro, negativ	

#### **Reproduction toxicity**

Based on the available information, the classification criteria are not fulfilled.

#### - Fertility

Substance		
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7		
NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed		
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9		
NOAEL, oral, Rat, 1000 mg/kg bw/day, In vivo study, negativ		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0		
NOAEL, oral, Rat, 1000 mg/kg bw/d, no adverse effect observed		

#### - Development

11.2

- Development			
Substance	Substance		
Destillates	Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7		
NOAEL, or	NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed		
Distillates (	Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9		
NOAEL, or	al, Rat, 1000 mg/kg bw/day, In vivo study, negativ		
Carcinogenicity	Based on the available information, the classification criteria are not fulfilled.		
Aspiration hazard	Based on the available information, the classification criteria are not fulfilled.		
General remarks			
	Toxicological data of complete product are not available.		
2 Information on other haza	rde		
i mormation on other nazards			
11.2.1 Endocrine disrupting properties	Contains no ingredients with endocrine-disrupting properties.		
11.2.2 Other information	none		

# SWAG Autoteile GmbH 42117 Wuppertal

Date printed 05.03.2024, Revision 05.03.2024



Version 7.0. Supersedes version: 6.0 Page 12 / 16

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
EC50, (48h), Invertebrates, 100 mg/L
EL50, (72h), Algae, 100 mg/L
NOELR, (21d), Invertebrates, 4.45 mg/L
NOELR, (33d), fish, 10 mg/L
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
EL50, (48h), Invertebrates, 10 g/L
NOELR, (14d), fish, 1 mg/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), fish, 100 mg/L
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
EL50, (24h), Daphnia magna, >10000 mg/l (OECD 202)
LL50, (96h), Pimephales promelas, >100 mg/l (OECD 203)
NOEL, (21d), Daphnia magna, 10 mg/l (OECD 211)
NOEL, (72h), Pseudokirchneriella subcapitata, >100 mg/l (OECD 201)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOELR, (14d), fish, 1 g/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), fish, 100 mg/L
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
EC50, (48h), Daphnia magna, 5,4 mg/l (OECD 202)
EC50, (72h), Selenastrum capricornutum, 2,1 mg/l
EC50, (3h), Activated sludge, >10000 mg/l
IC50, (21d), Daphnia magna, >0,8 mg/l
LL50, (96h), Oncorhynchus mykiss, 4,5 mg/l
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
NOELR, (14d), fish, 1 mg/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), fish, 100 mg/L
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
LC50, (96h), Cyprinus carpio, >100 mg/l
EC50, (24h), Daphnia magna, >100 mg/l
EC50, (72h), Pseudokirchneriella subcapitata, >100 mg/l
NOEC, (72h), Pseudokirchneriella subcapitata, 100 mg/l
NOELR, (24h), Daphnia magna, >100 mg/l

#### 12.2 Persistence and degradability

Behaviour in environment<br/>compartmentsCan be separated out mechanically in purification plants.Behaviour in sewage plantCan be separated out mechanically in purification plants.Biological degradabilityThe product is not readily biodegradable.

## SWAG Autoteile GmbH 42117 Wuppertal

Date printed 05.03.2024, Revision 05.03.2024



Version 7.0. Supersedes version: 6.0 Page 13 / 16

#### 12.3 Bioaccumulative potential

No information available.

#### 12.4 Mobility in soil

No information available.

#### 12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

#### 12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

#### 12.7 Other adverse effects

Ecological data of complete product are not available. Do not discharge product unmonitored into the environment or into the drainage.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

#### Product

	Coordinate disposal with the authorities if necessary. Disposal in an incineration plant in accordance with the regulations of the local authorities. In according to RoHS!
Waste no. (recommended)	130205* mineral-based non-chlorinated engine, gear and lubricating oils
Contaminated packaging	
	Uncontaminated packaging may be taken for recycling.
	Packaging that cannot be cleaned should be disposed of as for product.
Waste no. (recommended)	150110* packaging containing residues of or contaminated by hazardous substances

#### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

Transport by land according to ADR/RID	not applicable
Inland navigation (ADN)	not applicable
Marine transport in accordance with IMDG	not applicable

Air transport in accordance with IATA not applicable

### 42117 Wuppertal



Date printed 05.03.2024, Revision 05.03.2024

Version 7.0. Supersedes version: 6.0	Page 14 / 16
--------------------------------------	--------------

14.2	UN proper shipping name Transport by land according to ADR/RID	NO DANGEROUS GOODS
	Inland navigation (ADN)	NO DANGEROUS GOODS
	Marine transport in accordance with IMDG	NOT CLASSIFIED AS "DANGEROUS GOODS"
	Air transport in accordance with IATA	NOT CLASSIFIED AS "DANGEROUS GOODS"
14.3	Transport hazard class(es) Transport by land according to ADR/RID	not applicable
	Inland navigation (ADN)	not applicable
	Marine transport in accordance with IMDG	not applicable
	Air transport in accordance with IATA	not applicable
14.4	Packing group Transport by land according to ADR/RID	not applicable
	Inland navigation (ADN)	not applicable
	Marine transport in accordance with IMDG	not applicable
	Air transport in accordance with IATA	not applicable
14.5	Environmental hazards	
	Transport by land according to ADR/RID	no
	Inland navigation (ADN)	no
	Marine transport in accordance with IMDG	no
	Air transport in accordance with IATA	no
14.6	Special precautions for user	
	Relevant information under SECTION 6 t	to 8.

#### 14.7 Maritime transport in bulk according to IMO instruments

not applicable

### SWAG Autoteile GmbH

42117 Wuppertal

Date printed 05.03.2024, Revision 05.03.2024



Version 7.0. Supersedes version: 6.0 Page 15 / 16

#### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental	I regulations/legislation specific for the substance or mixture
EEC-REGULATIONS	2008/98/EG (2000/532/EG ); 2010/75/EU; 2004/42/EG; (EG) 648/2004; (EG) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EWG ((EG) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014; (EU) 2019/1148; (EU) 2019/1021
- Comment on component parts	Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
- Annex I (REACH)	The product is not subject to Annex I restrictions.
- Annex XIV (REACH)	According to Annex XIV of Regulation (EC) 1907/2006 (REACH) the product does not contain any substances $\ge 0.1\%$ that are subject to authorisation.
- Annex XVII (REACH)	According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product contains $\ge 0.1\%$ of substances with the following restrictions. 75
	According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product is subject to the following restrictions. 3
TRANSPORT-REGULATIONS	ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024)
NATIONAL REGULATIONS (UK):	EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK REACH; GB CLP.
<ul> <li>Observe employment restrictions for people</li> </ul>	Observe employment restrictions for young people.
- VOC (2010/75/CE)	0 %
15.2 Chemical safety assessment	
	For this product a chemical safety assessment has not been carried out.
SECTION 16: Other information	
16.1 Hazard statements (SECTION 3)	

H413 May cause long lasting harmful effects to aquatic life. H373 May cause damage to organs through prolonged or repeated exposure.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects. H318 Causes serious eye damage.

H315 Causes skin irritation.

H304 May be fatal if swallowed and enters airways.

42117 Wuppertal

Date printed 05.03.2024, Revision 05.03.2024



Version 7.0. Supersedes version: 6.0 Page 16 / 16

#### 16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

EL50 = Median effective loading

ELINCS = European List of Notified Chemical Substances

EmS = Emergency Schedules

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

- IUCLID = International Uniform ChemicaL Information Database
- IVIS = In vitro irritation score
- LC50 = Lethal concentration, 50% LD50 = Median lethal dose
- LC0 = lethal concentration, 0%
- LOAEL = lowest-observed-adverse-effect level

LL50 = Median lethal loading

LQ = Limited Quantities

MARPOL = International Convention for the Prevention of Marine Pollution from Ships NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value - time-weighted average

TLV®STEL = Threshold limit value - short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

#### 16.3 Other information

Classification procedureSkin Sens. 1: H317 May cause an allergic skin reaction. (Calculation method)Modified position1.3, 3.2, 5.1, 6.1, 8.1, 8.2, 9.1, 11.1, 11.2, 12.6, 12.7, 15.1, 16.2, 16.3