



ENGINE CLEANER

OILS & CHEMICALS | 29008

Functions

The main function of this additive is to clean the mechanical components inside the engine. The deposits will be dissolve which will reduce the friction of the moving parts and the wear.

Purpose

- · wear protection
- · fuel economy
- cleaning
- · improvement of compression



SYMPTOMS

- · oil pressure lamp lights up
- · engine jerks, rough idling
- · Increased oil consumption
- · Loss of power



REASONS FOR FAILURE

• silty engine



CONSEQUENTIAL DAMAGES

· engine damage due to silt



USAGE

- add to the used oil before changing it and let the engine run for 10-15 minutes
- drain old oil and add new oil and oil filter according to manufacturer's instructions**
- compatible with all conventional engine oils
- sufficient for 4 L engine oil
- suitable for all petrol and diesel engines



i.a. fitting for un

universal

X-Ref universal*

V60-1011

before use





after use







OILS & CHEMICALS FROM VAICO

You can find more information at www.vierol-shop.de

- optimum filling due to the supplied spout
- · improved exhaust emmissions
- · high operating reliability

^{*} For detailed vehicle information, please refer to the vehicle lists under www.vierol-shop.de. ** Dispose of waste oil in accordance with local regulations.

Our general terms and conditions of sale and delivery as well as our warranty conditions apply, which are available for download on our website. Errors excepted. Reference numbers and names, with the exception of VIEROL AG, are for comparison only and may not be disclosed in invoices. They are non-binding and no indication of origin. © VIEROL AG