

WOLF VITALTECH OW-40 SP

31/05/2024
16165

This fully synthetic engine oil meets the new API SP specification. The low viscosity grade SAE OW-40 enables the engine to run at high fuel-efficiency. This engine oil delivers excellent wear protection and engine cleanliness.

APPLICATIONS

This lubricant is designed for use in the most recent gasoline and diesel turbocharged cars or light duty vehicles. It is particularly developed for downsized Turbocharged Gasoline Direct Injection (TGDI) engines to mitigate LSPI (Low Speed Pre Ignition).

FEATURES

Cold start: excellent fluidity at low temperature.

Fuel economy: lower fuel consumption and CO2 emissions.

Total engine protection: outstanding engine cleanliness and durability.

SPECIFICATIONS

ACEA	A3/B4	MB	229.3
API	CF	MB	229.5
API	SP	PORSCHE	A40
BMW	LOGLIFE-01	RENAULT	RN 0700
FIAT	9.55535-Z2	RENAULT	RN 0710
FORD	WSS-M2C937-A	VW	502 00
MB	226.5	VW	505 00

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.845
Kinematic viscosity at 40°C	ASTM D445	mm²/s	61.9
Kinematic viscosity at 100°C	ASTM D445	mm²/s	12.7
Viscosity index	ASTM D2270		210
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	12.5
Pour point	ASTM D6892	°C	-48
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

