

WOLF VITALTECH 75W80 MULTI VEHICLE

11/08/2023
2211

This is a high quality mineral transmission oil, suitable for nearly all manual gearboxes of passenger cars. It is especially suitable as a replacement for specific OEM original oils and reduces the complexity and storage of gearbox oils. Tested under strict conditions, this oil satisfies the general performance requirements of most car makers and models, in all weather conditions.

APPLICATIONS

Tested under strict conditions, this oil meets the general performance requirements of most brands and models in all weather conditions.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: significantly extended transmission life
Extended oil life: proven resistance to oil degradation

PERFORMANCE

API	GL-4 +	MB	235.1
FIAT	9.55550-MX3	NISSAN	MT-XZ
FIAT	9.55550-MZ1	PSA	9730 A8
FORD	ESD-M2C186-A	PSA	B71 2330
FORD	WSD-M2C200-D	VOLVO	97308
GM	1940182	VOLVO	97309
GM	1940768	VOLVO	97310
HONDA	MTF 94		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.871
Kinematic viscosity at 40°C	ASTM D445	mm²/s	45.8
Kinematic viscosity at 100°C	ASTM D445	mm²/s	9.1
Viscosity index	ASTM D2270		185
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	142.000
Flash Point COC	ASTM D92	°C	205

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

