

WOLF CORS 15W-40

14/11/2023
3502

High performance formulation specifically developed for the lubrication of equipment used in construction, agriculture and public works machines. Particularly suited for use with lower quality fuels, with high sulfur content. It covers a wide set of applications such as engines, hydraulic systems, manual and powershift transmissions.

APPLICATIONS

Engine application: This higher TBN oil is advised for the lubrication of heavy duty diesel low-emission engines without particulate filter (Euro II, Euro III and some Euro IV engines). Gearboxes, powershift or manual, power take-off. Hydraulic systems of agricultural tractors and off-highway equipment.

FEATURES

Total engine protection: outstanding engine cleanliness and durability

Anti-wear and oxidation stability: proven protection of critical parts

SPECIFICATIONS

| | | | |
|-------------|------------------------|---------------|----------------|
| ACEA | E5 | DAIMLER TRUCK | DTFR 15B110 |
| ACEA | E7 | DEUTZ | DQC-III-10 |
| API | CH-4 | DEUTZ | DQC-III-18 |
| API | CI-4 | GLOBAL | DHD-1 |
| API | GL-4 | JCMA | HK 68W |
| ISO | VG 68 (After 100h)/HV | KOMATSU | CLUTCH: TO-40 |
| JASO | DH-1 | KOMATSU | HO-68 |
| ALLISON | C4 | MAN | M3275 |
| CASE | MS1230 (Hot Countries) | MB | 228.3 |
| CATERPILLAR | ECF-2 | MTU | Oil Category 2 |
| CATERPILLAR | TO-4 | NH | NH 330H |
| CATERPILLAR | TO-4M | RENAULT | RLD |
| CUMMINS | CES 20076 | RENAULT | RLD-2 |
| CUMMINS | CES 20077 | VOLVO | VDS-3 |
| CUMMINS | CES 20078 | ZF | TE-ML 07D |

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.890 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 101 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 13.9 |
| Viscosity index | ASTM D2270 | | 139 |
| B.N. (HClO ₄ method) | ASTM D2896 | mg KOH/g | 15.4 |
| Pour point | ASTM D6892 | °C | -36 |
| Flash Point COC | ASTM D92 | °C | 220 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

